


Concord

STERLING IP65 IK10 1325LM 830 SILVER
4063833



Features

- Led exterior bulkhead, Unique feature allowing a choice between High Output or High Efficiency with the flick of a switch, die-cast aluminium body, 684/1325LM, 9/17W, 76/78LM/W, 3000K, Driver Current: 350/750mA, CRI80, Non dimmable, IP65, IK10, lifespan 100,000hrs (L70:B50), (HxWxD) 350 x 350 x 128mm, 3.4kg, 3 step MacAdam ellipse, RAL 9006, Class 1, 230V, energy class: A++, A+, A


Product Overview

Product name	STERLING IP65 IK10 1325LM 830 SILVER
Technology	LED
Cap/Base	N/A
Environment	Indoor, Outdoor
E-number FI	4579259
Fixture luminous flux (lm)	684/1325
Luminaire efficacy (lm/W)	78
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Photobiological Risk Group	RG1
Total power consumption (W)	9/17
Electrical protection	Class I
Housing colour	Silver
IP rating	IP65
IK rating	IK10
Product EAN number	5026524638333
Warranty	5 years

Concord

STERLING IP65 IK10 1325LM 830 SILVER
4063833

Photometry



Technical drawings

