

## UFH-B0606-M: 1 f ball valve with 1 f swivel nut and washer



### Commercial information

UFH-B is a ball valve set (1"F) with a nut (1"F) that includes a seal

- Brass
- Ball valve set (blue and red)

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 66 mm    |
| Length     | 64 mm    |
| Width      | 33 mm    |
| Net weight | 0.649 kg |

#### Certificates

#### Applications

Underfloor Heating

#### Solutions

Underfloor heating, Building installations, Industry, Utility

## Technical characteristics

|                                     |       |                                  |                      |
|-------------------------------------|-------|----------------------------------|----------------------|
| Housing material                    | Brass | Diameter bolt hole               | 25                   |
| Surface protection housing          | None  | Outer pipe diameter connection 1 | 26 Millimetre        |
| Material ball seal                  | Other | Outer pipe diameter connection 2 | 26 Millimetre        |
| Material ball                       | Brass | Medium temperature (continuous)  | 5 95 Degrees celsius |
| Surface protection ball             | None  | Wrench width                     | 0 Millimetre         |
| With coupling connection 1          | ✗     | Wrench width union nut           | 0 Millimetre         |
| With coupling connection 2          | ✗     |                                  |                      |
| With drain valve                    | ✗     |                                  |                      |
| With drain possibility (connection) | ✗     |                                  |                      |
| With filter                         | ✗     |                                  |                      |
| With thermometer                    | ✗     |                                  |                      |
| With insulation shell               | ✗     |                                  |                      |
| UL quality mark                     | ✗     |                                  |                      |
| ULC quality mark                    | ✗     |                                  |                      |
| FM quality mark                     | ✗     |                                  |                      |
| LPCB quality mark                   | ✗     |                                  |                      |
| Fire-safe                           | ✗     |                                  |                      |
| Medically clean                     | ✗     |                                  |                      |
| Grease-free                         | ✗     |                                  |                      |
| Full bore                           | ✓     |                                  |                      |
| VdS quality mark                    | ✗     |                                  |                      |
| DVGW quality mark for gas           | ✗     |                                  |                      |
| KIWA certified                      | ✗     |                                  |                      |
| Type approval according to BBR/EKS  | ✗     |                                  |                      |