





















#### **Features**

 Simple and slick integral design with no driver box and without any visible screws Improved thermal resistance with in-track driver, ideal for retail applications Extremely precise light beams due to the high-quality lenses Special LED light source for VEGETABLE applications, the fruit and vegetable counter enhances the quality and genuineness of fresh products, bright tones highlight the colours of vegetables Die-cast aluminium body, Beam angle: 36°, additional lenses 24° and 54° beam angle included in the packaging, Textured black finishing colour Light color temperature: 5000K, Special spectrum for FOOD applications System power: 40W, Fixture lumen output: 4300lm, efficacy: 108lm/W, LED chromacity: 3 step MacAdam ellipse LED source (SDCM3), IR/UV free light source without heat radiation Operating voltage 220-240V / 50-60Hz, electronic driver, non-dimmable. ultra low LED flickering rate (5% or less) Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrack Electrical protection: Class II. Degree of protection: IP20, suitable for indoor environment only Horizontal rotation: 345°, vertical tilt: 90° Nominal product dimensions: D.91mmx150mm 5 years warranty Recycling instructions for extra lens in this product: please contact us for recycling instructions or disposal.

#### **Product Overview**


Product name	PIXO LARGE FOOD VEGETABLE NB MB WB BLACK
Technology	LED
Cap/Base	N/A
Housing	Aluminium



### 0004601

Mount	Track mounting
General application	Museums & Galleries, Office, Residential &
	Consumer, Retail
ETIM Class	EC001744
Fixture luminous flux (lm)	4300
Luminaire efficacy (Im/W)	108
Correlated colour temperature (k)	5000
Light colour	N/A
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Beam Angle (°)	36
Photobiological Risk Group	RG1
Total power consumption (W)	40
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Housing colour	Black
IP rating	IP20
IK rating	IK03
Product EAN number	5410288046013
Warranty	5 years
Dimming method	N/A

### **Technical drawings**



#### **Data table**

**GENERAL DATA** 



Product name	PIXO LARGE FOOD VEGETABLE NB MB WB BLACK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
General application	Museums & Galleries, Office, Residential & Consumer, Retail
Operating temperature range (°C)	25°C+25°C
ETIM Class	EC001744
Warranty	5 years

#### **OPTICAL DATA**

Fixture luminous flux (lm)	4300
Luminaire efficacy (lm/W)	108
Correlated colour temperature (k)	5000
Light colour	N/A
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Beam Angle (°)	36
Distribution type	Symmetric
Photobiological Risk Group	RG1

#### **ELECTRICAL DATA**

Total power consumption (W)	40
Current (A)	0.17
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100%	15
dimming level) < xx.x %	
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current



Dimmable	No
Dimming method	N/A
Inrush Current (A)	48
Inrush Duration (µs)	4
Energy Efficiency Class (A->G) of	D
contained light source	
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	24
Max. products per 13A C Breaker	26
Max. products per 16A C Breaker	32
Max. products per 20A C Breaker	40
Max. products per 10A B Breaker	15
Max. products per 13A B Breaker	16
Max. products per 16A B Breaker	20
Max. products per 20A B Breaker	25

#### **LIFETIME DATA**

Lifespan L70 B50	100000
Lifespan L80 B50	85000
Lifespan L90 B50	41000

#### PHYSICAL DATA

Housing colour	Black
IP rating	IP20
IK rating	IK03
Diffuser finish	Other
Diffuser material	None
Reflector finish	High-gloss
Nominal Product Length (mm)	150
Nominal Product Diameter (mm)	91
Weight (kg)	0.74

#### **PACKAGING**

**Product EAN number** 5410288046013



Packaging single length / height (cm)	21.5
Packaging single width (cm)	12.7
Packaging single depth (cm)	22.3
DUN14 (inner)	15410288046010
Units per outer package	8
Packaging outer length / height (cm)	53.0
Packaging outer width (cm)	44.5
Packaging outer depth (cm)	25.0

#### **SAFETY DATA**

Glow Wire Test (°C)	650
Optimal operating condition (°C)	25-25
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No