

## VB-EK05: Ball valve, 2 x eurocone connection



### Commercial information

Brass ball valve with 2x euro cone connection, PN 25

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 35 mm    |
| Length     | 50 mm    |
| Width      | 40 mm    |
| Net weight | 0.020 kg |

#### Certificates

#### Applications

Potable water, Heating, Sanitary

#### Solutions

Building installations, Industry, Utility

## Technical characteristics

|                                        |                                                   |                                    |                        |
|----------------------------------------|---------------------------------------------------|------------------------------------|------------------------|
| Housing material                       | Brass                                             | Medium temperature<br>(continuous) | -10 95 Degrees celsius |
| Material quality                       | CuZn40Pb2 (CW617N)                                |                                    |                        |
| Surface protection housing             | None                                              |                                    |                        |
| Material ball                          | Stainless steel                                   |                                    |                        |
| Material spindle                       | Brass                                             |                                    |                        |
| Material primary spindle seal          | Ethylene-propylene diene monomer<br>rubber (EPDM) |                                    |                        |
| With drain possibility<br>(connection) | ✗                                                 |                                    |                        |
| UL quality mark                        | ✗                                                 |                                    |                        |
| ULC quality mark                       | ✗                                                 |                                    |                        |
| FM quality mark                        | ✗                                                 |                                    |                        |
| LPCB quality mark                      | ✗                                                 |                                    |                        |
| Fire-safe                              | ✗                                                 |                                    |                        |
| Medically clean                        | ✗                                                 |                                    |                        |
| Grease-free                            | ✗                                                 |                                    |                        |
| KIWA certified                         | ✗                                                 |                                    |                        |