





















Features

 Simple and slick integral design with no driver box and without any visible screws Improved thermal resistance with in-track driver, ideal for retail applications Extremely precise light beams due to the high-quality lenses Special LED light source for FISH applications, cool shades enhance shine of the fish and brilliance of the ice, fish and seafood are more appealing Die-cast aluminium body, Beam angle: 36°, additional lenses 24° and 54° beam angle included in the packaging, Textured black finishing colour Light color temperature: 6500K, Special spectrum for FOOD applications System power: 40W, Fixture lumen output: 5000lm, efficacy: 125lm/W, LED chromacity: 3 step MacAdam ellipse LED source (SDCM3), IR/UV free light source without heat radiation Operating voltage 220-240V / 50-60Hz, electronic driver, non-dimmable, ultra low LED flickering rate (5% or less) Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrack Electrical protection: Class II. Degree of protection: IP20, suitable for indoor environment only Horizontal rotation: 345°, vertical tilt: 90° Nominal product dimensions: D.91mmx150mm 5 years warranty Recycling instructions for extra lens in this product: please contact us for recycling instructions or disposal.


Product Overview

| Product name | PIXO LARGE FOOD FISH NB MB WB BLACK |
|--------------|-------------------------------------|
| Technology | LED |
| Cap/Base | N/A |
| Housing | Aluminium |
| Mount | Track mounting |



| General application | Museums & Galleries, Office, Residential & Consumer, Retail |
|-----------------------------------|---|
| ETIM Class | EC001744 |
| Fixture luminous flux (Im) | 5000 |
| Luminaire efficacy (lm/W) | 125 |
| Correlated colour temperature (k) | 6500 |
| Light colour | N/A |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | 3 |
| Beam Angle (°) | 36 |
| Photobiological Risk Group | RG1 |
| Total power consumption (W) | 40 |
| Electrical protection | Class II |
| Control gear type | LED driver constant current |
| Dimmable | No |
| Housing colour | Black |
| IP rating | IP20 |
| IK rating | IK03 |
| Product EAN number | 5410288045993 |
| Warranty | 5 years |
| Dimming method | N/A |

Technical drawings



Data table

GENERAL DATA



| Product name | PIXO LARGE FOOD FISH NB MB WB BLACK |
|----------------------------------|--|
| Technology | LED |
| Cap/Base | N/A |
| Housing | Aluminium |
| Mount | Track mounting |
| General application | Museums & Galleries, Office, Residential & |
| | Consumer, Retail |
| Operating temperature range (°C) | 25°C+25°C |
| ETIM Class | EC001744 |
| Warranty | 5 years |

OPTICAL DATA

| Fixture luminous flux (lm) | 5000 |
|-----------------------------------|-----------|
| Luminaire efficacy (lm/W) | 125 |
| Correlated colour temperature (k) | 6500 |
| Light colour | N/A |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | 3 |
| Beam Angle (°) | 36 |
| Distribution type | Symmetric |
| Photobiological Risk Group | RG1 |

ELECTRICAL DATA

| Total power consumption (W) | 40 |
|--|-----------------------------|
| Current (A) | 0.17 |
| Primary Supply/Product voltage - min (V) | 220.0 |
| Primary Supply/Product voltage - max (V) | 240.0 |
| Lamp power factor | 0.9 |
| THD (at 230 V, 50 Hz, full load, at 100% | 15 |
| dimming level) < xx.x % | |
| Electrical protection | Class II |
| Control gear required | No |
| Control gear type | LED driver constant current |
| Dimmable | No |

Page 3 of 5



| Dimming method | N/A |
|-----------------------------------|---------|
| Inrush Current (A) | 48 |
| Inrush Duration (µs) | 4 |
| Energy Efficiency Class (A->G) of | С |
| contained light source | |
| Nominal Frequency (Hz) | 50/60Hz |
| Max. products per 10A C Breaker | 24 |
| Max. products per 13A C Breaker | 26 |
| Max. products per 16A C Breaker | 32 |
| Max. products per 20A C Breaker | 40 |
| Max. products per 10A B Breaker | 15 |
| Max. products per 13A B Breaker | 16 |
| Max. products per 16A B Breaker | 20 |
| Max. products per 20A B Breaker | 25 |

LIFETIME DATA

| Lifespan L70 B50 | 100000 |
|------------------|--------|
| Lifespan L80 B50 | 85000 |
| Lifespan L90 B50 | 41000 |

PHYSICAL DATA

| Housing colour | Black |
|-------------------------------|------------|
| IP rating | IP20 |
| IK rating | IK03 |
| Diffuser finish | Other |
| Diffuser material | None |
| Reflector finish | High-gloss |
| Nominal Product Length (mm) | 150 |
| Nominal Product Diameter (mm) | 91 |
| Weight (kg) | 0.74 |

PACKAGING

| Product EAN number | 5410288045993 |
|---------------------------------------|---------------|
| Packaging single length / height (cm) | 21.5 |



| Packaging single width (cm) | 12.7 |
|--------------------------------------|----------------|
| Packaging single depth (cm) | 22.3 |
| DUN14 (inner) | 15410288045990 |
| Units per outer package | 8 |
| Packaging outer length / height (cm) | 53.0 |
| Packaging outer width (cm) | 44.5 |
| Packaging outer depth (cm) | 25.0 |

SAFETY DATA

| Glow Wire Test (°C) | 650 |
|-------------------------------------|-------|
| Optimal operating condition (°C) | 25-25 |
| Special purpose lamp | No |
| Dry applications use only | No |
| Suitable for household illumination | No |