

BAP-SK2626: Ball valve with handle Push 26x26



Commercial information

Brass ball valve with 2 plug-in couplings. Handle has a red coating

Basic unit dimensions

Height	75 mm
Length	155 mm
Width	47 mm
Net weight	0.325 kg

Certificates

Applications

Potable water, Heating, Sanitary, Compressed air

Solutions

Building installations, Industry, Utility

Technical characteristics

Surface protection ball	None	Diameter bolt hole	26
Material secondary spindle seal	Ethylene-propylene diene monomer rubber (EPDM)	Outer pipe diameter connection 1	26 Millimetre
Nominal diameter connection 1	DN 20	Outer pipe diameter connection 2	26 Millimetre
Connection 1	Insert (push-fitting)	Medium temperature (continuous)	-10 70 Degrees celsius
With coupling connection 1	✓	Wrench width	0 Millimetre
Connection 2	Insert (push-fitting)	Wrench width union nut	0 Millimetre
With coupling connection 2	✓		
With drain valve	✗		
With drain possibility (connection)	✓		
With filter	✗		
With thermometer	✗		
Model	Straight		
With insulation shell	✗		
UL quality mark	✗		
ULC quality mark	✗		
FM quality mark	✗		
LPCB quality mark	✗		
Fire-safe	✗		
Medically clean	✗		
Grease-free	✗		
Full bore	✗		
VdS quality mark	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✗		
KIWA certified	✗		
Type approval according to BBR/EKS	✗		