

Protective Devices

Combined RCD/MCB Devices

PKNM-1 10VAC, 1+N-pole

Catalog



Powering Business Worldwide

SG13711



Description

- High-quality residual current device / miniature circuit breaker combination, line voltage-independent
- Contact position indicator red - green
- Guide for secure terminal connection
- 3-position DIN rail clip, permits removal from existing busbar system
- Comprehensive range of accessories can be mounted subsequently
- Rated currents 16, 20 and 32 A
- Tripping Characteristic C
- Rated breaking capacity 10 kA

SG13711


 $I_n/I_{\Delta n}$
(A)

Type
Designation

Article No. Units per
package
Type AC**10 kA, 1+N-pole****Conditionally surge current-proof 250 A, type AC****Characteristic C**

16/0.03	PKNM-16/1N/C/003-110VAC	286385	1/60
20/0.03	PKNM-20/1N/C/003-110VAC	294128	1/60
32/0.03	PKNM-32/1N/C/003-110VAC	286386	1/60
25/003	PKNM-25/1N/B/003-G/A	182889	1/60
32/003	PKNM-32/1N/B/003-G/A	182890	1/60

Specifications | Combined RCD/MCB Devices PKNM-110VAC, 1+N-pole**Description**

- Combined RCD/MCB Devices
- Line voltage-independent tripping
- Compatible with standard busbar
- Twin-purpose terminal (lift/open-mouthed) above and below
- Busbar positioning optionally above or below
- Free terminal space despite installed busbar
- Guide for secure terminal connection
- Switching toggle (MCB component) in colour designating the rated current
- Contact position indicator red - green
- Comprehensive range of accessories can be mounted subsequently
- The test key "T" must be pressed every 6 month. The system operator must be informed of this obligation and his responsibility in a way that can be proven (self-adhesive RCD-label enclosed). The test interval of 6 month is valid for residential and similar applications. Under all other conditions (e.g. damply or dusty environments), it's recommended to test in shorter intervals (e.g. monthly).
- Pressing the test key "T" serves the only purpose of function testing the residual current device (RCD). This test does not make earthing resistance measurement (R_E), or proper checking of the earth conductor condition redundant, which must be performed separately.

Accessories:


Auxiliary switch for subsequent installation	ZP-IHK	286052
	ZP-WHK	286053
Tripping signal switch for subsequent installation	ZP-NHK	248437
Shunt trip release	ZP-ASA/..	248438, 248439
Additional terminal 35 mm ²	BB-UL-TEPA/35	169823

Technical Data


PKNM-110VAC, 1+N-pole	
Electrical	
Design according to	IEC/EN 61009
Current test marks as printed onto the device	
Line voltage-independent tripping	instantaneous 250 A (8/20 μ s), surge current proof
Rated voltage	U_e 110 V AC, 50 Hz
Operational voltage range	94-121 V
Rated tripping current	$I_{\Delta n}$ 30 mA
Rated non-tripping current	$I_{\Delta no}$ 0.5 $I_{\Delta n}$
Rated insulation voltage	U_i 440 VAC
Sensitivity	AC
Selectivity class	3
Rated breaking capacity	I_{cn} 10 kA
Rated current	16, 20, 32 A
Rated impulse withstand voltage	U_{imp} 4 kV (1.2/50 μ s)
Characteristic	C
Maximum back-up fuse (short-circuit)	100 A gL (>10 kA)
Endurance	
electrical components	$\geq 4,000$ switching operations
mechanical components	$\geq 20,000$ switching operations
Mechanical	
Frame size	45 mm
Device height	80 mm
Device width	35 mm (2 MU)
Mounting	3-position DIN rail clip, permits removal from existing busbar system
Degree of protection, switch	IP20
Degree of protection, built-in	IP40
Upper and lower terminals	open-mouthed/lift terminals
Terminal protection	finger and hand touch safe, DGUV VS3, EN 50274
Terminal capacity	1 - 25 mm ²
Terminal torque	2 - 2.4 Nm
Busbar thickness	0.8 - 2 mm
Operating temperature	-25°C to +40°C
Storage- and transport temperature	-35°C to +60°C
Resistance to climatic conditions	according to IEC/EN 61009

Connection diagram

1+N-pole



Dimensions (mm)



Eaton's electrical business is a global leader with deep regional application expertise in power distribution and circuit protection; power quality, backup power and energy storage; control and automation; life safety and security; structural solutions; and harsh and hazardous environment solutions. Through end-to-end services, channel and an integrated digital platform & insights Eaton is powering what matters across industries and around the world, helping customers solve their most critical electrical power management challenges.

For more information, visit [Eaton.com](https://www.eaton.com).



Eaton Industries (Austria) GmbH
Scheydgasse 42
1210 Vienna
Austria

Eaton
EMEA Headquarters
Route de la Longeraie 7
1110 Morges, Switzerland

© 2021 Eaton
All Rights Reserved
Publication No. CA019042EN
Article number 302727-MK
July 2021

Changes to the products, to the information contained in this document, and to prices are reserved; as are errors and omissions. Only order confirmations and technical documentation by Eaton is binding. Photos and pictures also do not warrant a specific layout or functionality. Their use in whatever form is subject to prior approval by Eaton. The same applies to trademarks (especially Eaton, Moeller, and Cutler-Hammer). The Terms and Conditions of Eaton apply, as referenced on Eaton Internet pages and Eaton order confirmations.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

