




## High and reliable energy yield for commercial PV rooftops

- ✓ Maximised energy output
- ✓ Smart and silent operation
- ✓ Enhanced performance
- ✓ Highest safety standards

The SMT G2 60kW string inverter presents an excellent solution for small and medium-sized commercial and industrial (C&I) applications. It is specifically designed to accommodate high-power PV modules, featuring 4 MPPTs and a high input current of 21A per DC string, resulting in improved overall yield. With a weight of only 42kg and exceptionally quiet operation, it's perfectly suited for installations in noise-sensitive environments.

-  21A per string & 150% PV oversizing
-  AI-driven AFCI 3.0 for safety
-  Operate quietly at under 50dB



Technical Data		GW60K-SMT-G20
<b>Input</b>		
Max. Input Voltage (V)		1100 <sup>*1</sup>
MPPT Operating Voltage Range (V) <sup>*2</sup>		160 ~ 1000
Start-up Voltage (V)		180
Nominal Input Voltage (V)		600
Max. Input Current per MPPT (A)		42
Max. Short Circuit Current per MPPT (A)		52.5
Number of MPP Trackers		4
Number of Strings per MPPT		2
<b>Output</b>		
Nominal Output Power (kW)		60
Nominal Output Apparent Power (kVA)		60
Max. AC Active Power (kW)		66
Max. AC Apparent Power (kVA)		66
Nominal Output Voltage (V)		220 / 380, 230 / 400, 3L / N / PE or 3L / PE
Output Voltage Range (V)		323 ~ 456
Nominal AC Grid Frequency (Hz)		50 / 60
AC Grid Frequency Range (Hz)		45 ~ 55 / 55 ~ 65
Max. Output Current (A)		100.0 @ 220V, 95.7 @ 230V
Power Factor		~1 (Adjustable from 0.8 leading to 0.8 lagging)
Max. Total Harmonic Distortion		<3%
<b>Efficiency</b>		
Max. Efficiency		98.8%
European Efficiency		98.3%
<b>Protection</b>		
PV String Current Monitoring		Integrated
PV Insulation Resistance Detection		Integrated
Residual Current Monitoring		Integrated
PV Reverse Polarity Protection		Integrated
Anti-islanding Protection		Integrated
AC Overcurrent Protection		Integrated
AC Short Circuit Protection		Integrated
AC Overvoltage Protection		Integrated
DC Switch		Integrated
DC Surge Protection		Type II (Type I + II optional)
AC Surge Protection		Type II
AFCI		Optional
Remote Shutdown		Integrated
PID Recovery		Optional
Power Supply at Night		Optional
I-V Curve Scan		Optional
<b>General Data</b>		
Operating Temperature Range (°C)		-30 ~ +60
Relative Humidity		0 ~ 100%
Max. Operating Altitude (m)		4000
Cooling Method		Smart Fan Cooling
User Interface		LED, LCD (Optional), APP
Communication		RS485, WiFi + LAN + Bluetooth
Communication Protocols		Modbus-RTU (SunSpec Compliant), Modbus-TCP
Weight (kg)		42
Dimension (W x H x D mm)		685 x 545 x 225
Topology		Non-isolated
Self-consumption at Night (W)		<1
Ingress Protection Rating		IP66
DC Connector		MC4 (4 ~ 6mm <sup>2</sup> )
AC Connector		OT / DT terminal (Max. 70mm <sup>2</sup> )
Mounting Method		Wall Mounted

\*1: When the input voltage ranges from 1000V to 1100V, the inverter will enter the standby state. When the input voltage returns to the MPPT operating voltage range, the inverter will resume normal operating state.

\*2: Please refer to the user manual for the MPPT Voltage Range at Nominal Power.

\*: Please visit GoodWe website for the latest certificates.