










Color: ■ light gray





Dimensions in mm
L = pole no. x pin spacing + 2.9 mmL1 = L + 6.5 mm

Male connector, 831 Series, solder pin dimensions 1 x 1.2 mm

Our male connector (item number 831-3627/108-000) is designed for seamless electrical installations. The item's dimensions are (68.9 x 18.8 x 29) mm (width x height x depth).

Tin is used for coating the contact surfaces. THT is used to assemble the pcb connector.

Notes	
Safety Information	The MCS – MULTI CONNECTION SYSTEM includes connectors without breaking capacity in accordance with DIN EN 61984. When used as intended, these connectors must not be connected/disconnected when live or under load. When used as intended, these connectors must not be connected/disconnected when live or under load. The circuit design should ensure header pins, which can be touched, are not live when unmated.
Variants:	Other pole numbers Protection against PCB mounting errors Other versions (or variants) can be requested from WAGO Sales or configured at https://configurator.wago.com/ .

Electrical data				
Ratings per		IEC/EN 60664-1		
Overvoltage category		III	III	II
Pollution degree		3	2	2
Nominal voltage		500 V	630 V	1000 V
Rated impulse withstand voltage		6 kV	6 kV	6 kV
Rated current		41 A	41 A	41 A
Approvals per		UL 1059		
Use group		B	C	D
Rated voltage		-	300 V	600 V
Rated current		-	42 A	5 A
Approvals per		CSA		
Use group		B	C	D
Rated voltage		-	300 V	600 V
Rated current		-	41 A	5 A



Connection Data		
Total number of potentials	7	Connection 1
Number of connection types	1	
Number of levels	1	
		Pole number 7

Physical data		
Pin spacing	7.62 mm / 0.3 inches	
Width	68.9 mm / 2.714 inches	
Height	18.8 mm / 0.74 inches	
Height from the surface	14.8 mm / 0.583 inches	
Depth	29 mm / 1.142 inches	
Solder pin length	4 mm	
Solder pin dimensions	1 x 1.2 mm	
Drilled hole diameter with tolerance	1.7 ^(+0.1) mm	

Mechanical data		
Variable coding	Yes	
Anti-rotation protection	Yes	

Plug-in connection		
Contact type (pluggable connector)	Male connector/plug	
Connector (connection type)	for PCB	
Mismating protection	Yes	
Mating direction to the PCB	0 °	
Locking of plug-in connection	Threaded flange	

PCB contact		
PCB contact	THT	
Solder pin arrangement	over the entire male connector (in-line)	
Number of solder pins per potential	3	

Material data		
Note (material data)	Information on material specifications can be found here	
Color	light gray	
Material group	I	
Insulation material (main housing)	Polyamide (PA66)	
Flammability class per UL94	V0	
Contact material	Electrolytic copper (E _{Cu})	
Contact Plating	Tin	
Fire load	0.348 MJ	
Weight	21.1 g	



Environmental requirements	
Limit temperature range	-60 ... +105 °C
Processing temperature	-35 ... +60 °C

Commercial data	
PU (SPU)	12 pcs
Packaging type	Box
Country of origin	PL
GTIN	4066966090000
Customs tariff number	85366930000

Product Classification	
UNSPSC	39121409
ETIM 9.0	EC002637
ETIM 10.0	EC002637
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant, No Exemption
SCIP notification number (Austria)	8af31e29-d125-4917-9bdf-5c0ea2690547
SCIP notification number (Belgium)	81bca80c-f728-4afb-8ace-59c1396affa7
SCIP notification number (Bulgaria)	a88fe73a-e90c-4be6-8d8a-4f33f55bfd92
SCIP notification number (Czech Republic)	d7bbaae3-265f-4ccc-ac66-6a4d5a455a88
SCIP notification number (Denmark)	046009df-a978-4360-879f-0cf1183f6995
SCIP notification number (Finland)	8b6c7816-be7a-4378-b50d-796f8f5a9044
SCIP notification number (France)	60f16464-4d97-4a26-bbb5-5b16615c3e7d
SCIP notification number (Germany)	93aabb66-d622-4cfb-a644-c1f709cb57bb
SCIP notification number (Hungary)	fc014adb-28f2-4609-b169-7e142328db91
SCIP notification number (Italy)	7258bca6-7661-40b4-9835-2d3a887952fb
SCIP notification number (Netherlands)	1b1aabb8-8070-4256-8d5f-6f3702c0e7ab
SCIP notification number (Poland)	0d344fa3-50e0-4193-a805-c0ed1c803eb8
SCIP notification number (Romania)	9a97eb04-6f3f-4e13-94a4-670c14eebbf5
SCIP notification number (Sweden)	21088881-3fe5-4e11-9894-5cc4af1eaeedc

Approvals / Certificates	
General approvals	



Approval	Standard	Certificate Name
CB DEKRA Certification B.V.	IEC 61984	NL-61360/M1
KEMA/KEUR DEKRA Certification B.V.	EN 61984	71-116057
UL Underwriters Laboratories Inc.	UL 1059	UL-US-2426356-0

Downloads

Environmental Product Compliance

Compliance Search			
Environmental Product Compliance	831-3627/108-000		

Documentation

Additional Information			
Technical Section	03.04.2019	pdf 2027.26 KB	

CAD/CAE-Data


CAD data	
2D/3D Models	
831-3627/108-000	

CAE data	
ZUKEN Portal	
831-3627/108-000	


PCB Design	
Symbol and Footprint via SamacSys	
831-3627/108-000	
Symbol and Footprint via Ultra Librarian	
831-3627/108-000	

Installation Notes


Coding



Break or cut off coding pin from female connector.



Insert coding pin into male header (break first) until it engages.



Coding a THT male header by inserting a coding pin.