

Product data sheet

Item No. 92.030.2253.0

Linect distributor GST18I3VN2P1N V WS

Lighting connector gesis LINECT, GST18i3, 3-pole, 1 Input, 1 Outlet, 1 interface to a lighting terminal-block with LINECT port. 250 V, 20 A. Tocontact luminaires with LINECT-interface to power circuits. Coding: white, housing: white



Item No.	92.030.2253.0
EAN	4049088092978
Order Unit	50 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	White
Marking of poles	

Model

Number of poles	3
Number of inputs	1
Number of outputs	2
Type of fastening	Yes
Degree of protection (IP)	IP40
Type of distributor	Combined distribution block

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Tin-plated

Dimensions

Length	71.6 mm
Width	52.6 mm
Height	45.2 mm

Technical drawing

Codierung A Mains

max. Bereich außerhalb der Leuchte / max. area outside of the luminaire

M 1:1

92.030.2253.0 01K a	
LINECT	