


Concord

Solstice 150 1300lm 940 SSC GB
2070236



Features

- The Solstice 150 1300lm 940 SSC GB is a high efficient SSC GB dimmable downlight luminaire, Colour rendering index Ra>90, Colour temperature: 4000K Neutral White, Class II, Protection rating IP40/IP20, Cut out dimensions: 150mm.



Product Overview


Product name	Solstice 150 1300lm 940 SSC GB
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
E-number FI	4262062
Fixture luminous flux (lm)	1300
Luminaire efficacy (lm/W)	87
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	15
Electrical protection	Class II
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9005 - Jet black

Concord

Solstice 150 1300lm 940 SSC GB
2070236

IP rating	IP40/20
IK rating	IK02
Product EAN number	5025768702367
Warranty	5 years

Photometry



Technical drawings

