

Product data sheet

Item No. 92.207.2003.2

Cable assembly

geis® Connection cable female - free end; length: 2m; type GST18I4; 4-pole; 250/400 V / 16 A; colour of coding: white with white strain-relief; cable: H05VV-F 4G1,5, colour: white



Item No.	92.207.2003.2
EAN	4049088187841
Order Unit	25 Piece(s)

Certificates / Approvals



Technical data

**General**

Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

**Model**

Number of poles	4
Nominal cross section conductor	1.5 mm <sup>2</sup>
Degree of protection (IP)	IP40
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F



Cable colour	Black
Cable diameter	9.2 mm
Version of cable	Female - free end
Type of cord set	Connection cable
Version cable end 1	GST18i4 socket
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	60 °C
Insulation components continuous temperature	100 °C

Technical drawing

Pol	Aderfarbe
pole	colour of core
L2	schwarz / black
N	blau / blue
⊕	grün-gelb / green-yellow
L1	braun / brown

.F	Farbe colour	Codierung +X Buchse Female	Kabelfarbe / cable colour
.1	schwarz black	2 N PE 1	schwarz black
.2	weiß white	2 N PE 1	weiß white
.3	grau grey	2 N PE 1	schwarz black

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) exampel (colour: black)	Typ type
92.207.XX03.F	XX in dm-Schritten	92.207.1003.1 = 10dm/L = 1000mm	GST18i4KSB- 15 10SW
U2.207.XX03.F	XX in m-Schritten	U2.207.1203.1 = 12m/L=12000mm	GST18i4KSB- 15 X10SW

Weitere Daten siehe Katalog  
further data see catalog

Typ/type: GST18i4KSB- 15 .. WS = weiß/white  
GR01 = grau/grey

wieland

PRE-ASSEMBLED CABLE  
KONFEKTLEITUNG  
Buchse/female - freies Ende/free end 1,5mm  
Schraubanschluß/screw connection 250V