

Motion detector, 230 V, 16 m, 180°, IP54, with orientable lens, for surface mounting, white

350-20050



4 year warranty



230 V



stand-alone



IP54



N.O.



180°




ø 16 m from a height of 3 m



2 m - 3 m



surface-mounting



This 1-channel outdoor motion detector is especially suitable for use in a driveway or garden. The detection range can be set to between 0 and 16 m. The detection area can be divided using an adjustable protection mask. The motion sensor can be precisely aimed. The device has a built-in light sensor and switches the lighting on automatically or manually with an N.C. push button (to be ordered separately). After the pre-set time delay, the light is switched off automatically. This motion detector has an IP54 protection degree and complies with the European directives for EMC and safety, EN 60669-2-1.

Colour: white


Compatible secondary detectors:

Compatible master detectors:

- Sustainable
- Functional
- Elegant
- Simple installation
- Energy saving
- Greater comfort
- Improved burglary protection

Motion detector for use in carports, gardens, etc.

Detection range




H	A Across	B Towards
2 m	11 m	5.5 m
2.5 m	14 m	7 m
3 m	16 m	8 m

- The outdoor motion detector is fitted with a built-in light sensor; the lighting only turns on if the detector detects motion in the detection range and the level of daylight is below the programmed lux value.
- The lighting remains on while motion is detected.
- The built-in time switch allows you to set the desired switch-off delay. The lighting will remain on throughout the disconnection time after the last movement has been detected.
- The sensor's lens can be covered with the cover mask provided, so you can divide the detection zone. The cover mask can be adapted according to the desired range.

Technical features

Configuration	stand-alone
Input voltage	230 Vac
Detector output	230 V (ON/OFF)
Switch-off delay	8 sec – 1,800 sec
Maximum MCB rating	-10
Detection angle	180 °
Detection range (PIR)	ø 16 m from a height of 3 m
Minimum ambient temperature	-20 °C
Maximum ambient temperature	+45 °C
Mounting method	surface mounting
Mounting height	2 m – 3 m
Colour	white
Dimensions (HxWxD)	70 mm x 90 mm x 130 mm
Protection degree standalone	IP54

Dimensions



Wiring diagram

