

## CU-10ZONERF-HC: Base module 10 zones heating/cooling, wireless



### Commercial information

HencoLogic Base module 10 zones heating/cooling, wireless

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 52 mm    |
| Length     | 365 mm   |
| Width      | 90 mm    |
| Net weight | 1.187 kg |

#### Certificates

#### Applications

Cooling, Heating, Underfloor Heating

#### Solutions

Underfloor heating, Building installations, Industry, Utility

## Technical characteristics

|                                         |                             |                                |                 |
|-----------------------------------------|-----------------------------|--------------------------------|-----------------|
| Networkable via radiographic (standard) | ✓                           | Output voltage                 | 230 Volt        |
| Networkable via radio (optional)        | ✓                           | Max. power per channel         | 1150 Voltampere |
| Connection for external antenna         | ✓                           | Reception frequency            | 868 Megahertz   |
| Smart control                           | ✓                           | Level of protection (IP value) | 20              |
| Suitable for heating                    | ✓                           | Max. contact voltage           | 230 Volt        |
| Contact type                            | Change-over                 | Max. contact load              | 5 Ampere        |
| Suitable for heating                    | ✓                           | Width                          | 90 Millimetre   |
| Suitable for cooling                    | ✓                           | Height                         | 52 Millimetre   |
| With time switch clock                  | ✓                           | Depth                          | 365 Millimetre  |
| With extra contact                      | ✓                           |                                |                 |
| Contact type                            | Change-over contact (NO/NC) |                                |                 |