

ToLEDo GLS

ToLEDo GLS V3 1521LM 840 E27 SL

0026652



Product features

- Compact and elegant design
- Suitable replacement for halogen, incandescent and compact fluorescent ball lamps
- Instant light at the flick of a switch
- Uniform light distribution
- Good colour rendering (CRI 80)
- Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
- Lower maintenance costs
- 15,000 hours average rated life



PRODUCT OVERVIEW

Product name	ToLEDo GLS V3 1521LM 840 E27 SL
Technology	LED
Watt (Rated) (W)	15
Lamp shape	Pear-shape
Type	ToLEDo GLS
Cap/Base	E27
Lamp finish	Frosted/Coated
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740482
Luminous flux (lm)	1521
Colour temperature (K)	4000
Light colour	Cool White
Colour Code	840
CRI (Ra)	80
Colour Consistency (SDCM)	6
Wattage (W)	15
Dimming method	N/A
Average life (Nominal) (h)	15000
Product EAN number	5410288266527

DATA TABLE

General data

Product name	ToLEDo GLS V3 1521LM 840 E27 SL
Technology	LED
Watt (Rated) (W)	15
Lamp shape	Pear-shape
Type	ToLEDo GLS
Cap/Base	E27
Lamp finish	Frosted/Coated
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959

ToLEDo GLS

ToLEDo GLS V3 1521LM 840 E27 SL
0026652

E-number FI 4740482

Optical data

Luminous flux (lm)	1521
Luminous flux (Rated) (lm)	1521
Colour temperature (K)	4000
Light colour	Cool White
Colour Code	840
CRI (Ra)	80
Colour Consistency (SDCM)	6
Adjustable chromaticity	N
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	15
Equivalent watt (W)	100
Starting time (max) (s)	0.05
Warm-up time to 60% of full light (max) (s)	< 1s => 60%
Lamp power factor	0.5
Control gear required	No
No. Of switching cycles before premature failures	>50000
Dimming method	N/A
Drive current (mA)	120

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Max. Lamp Diameter (mm) - D	66
Weight (kg)	0.103

Packaging

Single packaging type	Carton
Product EAN number	5410288266527
Packaging single length / height (cm)	14.6
Packaging single width (cm)	7.0
Packaging single depth (cm)	7.0
DUN14 (inner)	25410288266521
Units per inner package	6
Packaging inner length / height (cm)	22.7
Packaging inner width (cm)	15.4
Packaging inner depth (cm)	17.3
DUN14 (outer)	15410288266524
Units per outer package	60
Packaging outer length / height (cm)	81.0
Packaging outer width (cm)	24.2

ToLEDo GLS

ToLEDo GLS V3 1521LM 840 E27 SL

0026652

Packaging outer depth (cm)	38.4
----------------------------	------

Safety data

Breakage cleaning instructions	Not applicable
Recommendation for disposal at end of life	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Suitable for accent lighting	Yes

TECHNICAL DRAWINGS

