

## BAP-SV1610S: Stop valve DN10



### Commercial information

Henco stop globe valve in brass. With press connection

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 23 mm    |
| Length     | 75 mm    |
| Width      | 23 mm    |
| Net weight | 0.110 kg |

#### Certificates

#### Applications

Potable water, Heating, Sanitary, Compressed air

#### Solutions

Building installations, Industry, Utility

## Technical characteristics

|                                     |                                                       |                                  |                        |
|-------------------------------------|-------------------------------------------------------|----------------------------------|------------------------|
| Surface protection ball             | None                                                  | Diameter bolt hole               | 16                     |
| Material secondary spindle seal     | Ethylene-propylene diene monomer rubber (EPDM)        | Outer pipe diameter connection 1 | 16 Millimetre          |
| Nominal diameter connection 1       | DN 8                                                  | Outer pipe diameter connection 2 | 10 Millimetre          |
| Connection 1                        | Press sleeve                                          | Medium temperature (continuous)  | -10 70 Degrees celsius |
| With coupling connection 1          | ✓                                                     | Wrench width                     | 0 Millimetre           |
| Contour code connection 1           | TH/BE                                                 | Wrench width union nut           | 0 Millimetre           |
| Nominal diameter connection 2       | DN 10                                                 |                                  |                        |
| Connection 2                        | External thread conical BSPT-R (ISO 7-1 / EN 10226-1) |                                  |                        |
| With coupling connection 2          | ✓                                                     |                                  |                        |
| Sealing                             | Ethylene-propylene diene monomer rubber (EPDM)        |                                  |                        |
| With drain valve                    | ✗                                                     |                                  |                        |
| With drain possibility (connection) | ✓                                                     |                                  |                        |
| With filter                         | ✗                                                     |                                  |                        |
| With thermometer                    | ✗                                                     |                                  |                        |
| Model                               | Straight                                              |                                  |                        |
| With insulation shell               | ✗                                                     |                                  |                        |
| UL quality mark                     | ✗                                                     |                                  |                        |
| ULC quality mark                    | ✗                                                     |                                  |                        |
| FM quality mark                     | ✗                                                     |                                  |                        |
| LPCB quality mark                   | ✗                                                     |                                  |                        |
| Fire-safe                           | ✗                                                     |                                  |                        |
| Medically clean                     | ✗                                                     |                                  |                        |
| Grease-free                         | ✗                                                     |                                  |                        |
| Full bore                           | ✗                                                     |                                  |                        |
| KIWA certified                      | ✗                                                     |                                  |                        |