

Product data sheet Spirotech

Product name

EVSolar Expansion vessel 25L, hanging

Product properties

Safety expansion vessel for solar systems, with a flanged, replaceable and frost-proof bag membrane to hold the expansion medium. P max. 6 bar / T max. 70°C.

- Tested according to Pressure Equipment Directive 2014/68/EU
- Max. temperature at connection point: 70 °C
- Max. operating pressure: 6 bar

Article number

EVSolar25

Product image



Product dimensions

Product data sheet Spirotech

ETIM product data

| | |
|---------------------------------------|---|
| Height | 400 mm |
| Volume | 25 l |
| Colour | Green |
| Diameter | 360 mm |
| Medium temperature (continuous) | 0 - 70 °C |
| Max. operating pressure | 6 bar |
| Connection | External thread conical BSPT-R (ISO 7-1 / EN 10226-1) |
| With pressure gauge | No |
| With exchangeable membrane | Yes |
| Nominal diameter expansion connection | 3/4 inch (20) |
| Horizontal positioning | No |
| Suitable for central heating | No |
| Vertical positioning | Yes |

| | |
|--------------------------------------|--|
| With legs | No |
| Material membrane/bladder | Ethylene-propylene diene monomer rubber (EPDM) |
| With drain | No |
| With safety valve | No |
| With mounting material | Yes |
| Max. glycol mixture | 60 % |
| Suitable for tap water | No |
| Max. ethanol mixture | 60 % |
| Suitable for solar collector circuit | Yes |
| Pre-pressure | 3.5 bar |
| With fixed wall support | Yes |
| Suitable for cooling | No |

Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website.

