

ToLEDo GLS

ToLEDo GLS V6 1055LM 827 E27 SL

0026682



Product features

- Compact and elegant design
- Suitable replacement for halogen, incandescent and compact fluorescent GLS lamps
- Instant light at the flick of a switch
- Uniform light distribution
- Good colour rendering (CRI 80)
- Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
- Lower maintenance costs
- A+ energy rating



PRODUCT OVERVIEW

Product name	ToLEDo GLS V6 1055LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	11
Type	ToLEDo GLS
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740293
Warranty	3 years
Luminous flux (lm)	1055
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Beam Angle (°)	180
Wattage (W)	11
Average life (Nominal) (h)	15000
Product EAN number	5410288266824

DATA TABLE

General data

Product name	ToLEDo GLS V6 1055LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	11
Type	ToLEDo GLS
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740293

ToLEDo GLS

ToLEDo GLS V6 1055LM 827 E27 SL

0026682

Warranty	3 years
----------	---------

Optical data

Luminous flux (lm)	1055
Luminous flux (Rated) (lm)	1055
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Beam Angle (°)	180
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	11
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Lamp power factor	0.5
No. Of switching cycles before premature failures	>50000
Inrush Current (A)	3.3
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	120
Max. products per 16A C Breaker	201
Max. products per 20A C Breaker	252

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	120
Nominal Product Diameter (mm)	60
Weight (kg)	0.057

Packaging

Single packaging type	Carton
Product EAN number	5410288266824
Packaging single length / height (cm)	11.3
Packaging single width (cm)	6.4
Packaging single depth (cm)	6.4
DUN14 (inner)	25410288266828
Units per inner package	6
Packaging inner length / height (cm)	20.4
Packaging inner width (cm)	13.4
Packaging inner depth (cm)	13.7
DUN14 (outer)	15410288266821
Units per outer package	60
Packaging outer length / height (cm)	72.4
Packaging outer width (cm)	22.2

ToLEDo GLS

ToLEDo GLS V6 1055LM 827 E27 SL

0026682

Packaging outer depth (cm)	29.7
----------------------------	------

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

TECHNICAL DRAWINGS

