


PIXO ZOOM 2100LM 17D-60D 3CCT MULTIPOWER BLACK
0004521



Features

• Simple and slick integral design with no driver box and without any visible screws Improved thermal resistance with in-track driver, ideal for retail applications Extremely precise light beams due to the high-quality lenses Adjustable beam angle between 17° - 60° Die-cast aluminium body, Textured black finishing colour Light color temperature: 3CCT - 2700-3000-4000K, changeable from the adaptor System power: 25W, Fixture lumen output: 2100lm, efficacy: 84lm/W (90lm/W at 15W-60D) LED chromacity: 3 step MacAdam ellipse LED source measured at 2700K & 4000K (SDCM3), IR/UV free light source without heat radiation Operating voltage 220-240V / 50-60Hz, Multipower in-track driver, ultra low LED flickering rate (5% or less), Multipower adaptor module meets all installation needs with one single product selection and setting on adaptor - between 12W (300mA), 18W (450mA), 25W (600mA Max). Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrack Electrical protection: Class II. Degree of protection: IP20, suitable for indoor environment only Horizontal rotation: 345°, vertical tilt: 90° Nominal product dimensions: D.85mmx170mm 5 years warranty


Product Overview

Product name	PIXO ZOOM 2100LM 17D-60D 3CCT MULTIPOWER BLACK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting


PIXO ZOOM 2100LM 17D-60D 3CCT MULTIPOWER BLACK
0004521

General application	Museums & Galleries, Retail, Hospitality, Office
ETIM Class	EC001744
E-number FI	4279621
Fixture luminous flux (lm)	2100
Luminaire efficacy (lm/W)	84
Light colour	Warm White or Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Photobiological Risk Group	RG1
Total power consumption (W)	25
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Housing colour	Black
IP rating	IP20
IK rating	IK03
Product EAN number	5410288045214
Warranty	5 years
Dimming method	N/A


Photometry












PIXO ZOOM 2100LM 17D-60D 3CCT MULTIPOWER BLACK
0004521



PIXO ZOOM 2100LM 17D-60D 3CCT MULTIPOWER BLACK
0004521




PIXO ZOOM 2100LM 17D-60D 3CCT MULTIPOWER BLACK 0004521



PIXO ZOOM 2100LM 17D-60D 3CCT MULTIPOWER BLACK
0004521



Technical drawings



Data table

PIXO ZOOM 2100LM 17D-60D 3CCT MULTIPOWER BLACK 0004521

GENERAL DATA

Product name	PIXO ZOOM 2100LM 17D-60D 3CCT MULTIPOWER BLACK
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
General application	Museums & Galleries, Retail, Hospitality, Office
Operating temperature range (°C)	25°C...+25°C
ETIM Class	EC001744
E-number FI	4279621
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	2100
Luminaire efficacy (lm/W)	84
Light colour	Warm White or Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Distribution type	Symmetric
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	25
Current (A)	0.11
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	15
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current

PIXO ZOOM 2100LM 17D-60D 3CCT MULTIPOWER BLACK 0004521

Dimmable	No
Dimming method	N/A
Inrush Current (A)	48
Inrush Duration (µs)	200
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	20
Max. products per 13A C Breaker	26
Max. products per 16A C Breaker	32
Max. products per 20A C Breaker	40
Max. products per 10A B Breaker	13
Max. products per 13A B Breaker	16
Max. products per 16A B Breaker	20
Max. products per 20A B Breaker	25

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L70 B20	100000
Lifespan L70 B10	100000
Lifespan L80 B50	100000
Lifespan L80 B20	93000
Lifespan L80 B10	86000
Lifespan L90 B50	56000
Lifespan L90 B20	44000
Lifespan L90 B10	41000

PHYSICAL DATA

Housing colour	Black
IP rating	IP20
IK rating	IK03
Diffuser finish	Other
Diffuser material	None
Reflector finish	High-gloss



PIXO ZOOM 2100LM 17D-60D 3CCT MULTIPOWER BLACK
0004521

Nominal Product Length (mm)	170
Nominal Product Diameter (mm)	85
Weight (kg)	0.949

PACKAGING

Product EAN number	5410288045214
Packaging single length / height (cm)	24.0
Packaging single width (cm)	12.0
Packaging single depth (cm)	23.3
DUN14 (inner)	15410288045211
Units per outer package	8
Packaging outer length / height (cm)	50.5
Packaging outer width (cm)	50.0
Packaging outer depth (cm)	26.0

SAFETY DATA

Glow Wire Test (°C)	650
Optimal operating condition (°C)	25-25
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No