

Product data sheet Spirotech

Product name

EVSolar Expansion vessel 35L, hanging

Product properties

Safety expansion vessel for solar systems, with a flanged, replaceable and frost-proof bag membrane to hold the expansion medium. P max. 6 bar / T max. 70°C.

- Tested according to Pressure Equipment Directive 2014/68/EU
- Max. temperature at connection point: 70 °C
- Max. operating pressure: 6 bar

Article number

EVSolar35

Product image



Product dimensions

Product data sheet Spirotech

ETIM product data

Height	500 mm
Volume	35 l
Colour	Green
Diameter	360 mm
Medium temperature (continuous)	0 - 70 °C
Max. operating pressure	6 bar
Connection	External thread conical BSPT-R (ISO 7-1 / EN 10226-1)
With pressure gauge	No
With exchangeable membrane	Yes
Nominal diameter expansion connection	3/4 inch (20)
Horizontal positioning	No
Suitable for central heating	No
Vertical positioning	Yes

With legs	No
Material membrane/bladder	Ethylene-propylene diene monomer rubber (EPDM)
With drain	No
With safety valve	No
With mounting material	Yes
Max. glycol mixture	60 %
Suitable for tap water	No
Max. ethanol mixture	60 %
Suitable for solar collector circuit	Yes
Pre-pressure	3.5 bar
With fixed wall support	Yes
Suitable for cooling	No

Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website

