

Product data sheet

Item No. 92.207.4063.2

Cable assembly

geis® Connection cable female - free end; length: 4m; type GST18I4; 4-pole; 250/400 V / 16 A; colour of coding: white with white strain-relief; cable: H05Z1Z1-F 4G1,5, colour: white



Item No.	92.207.4063.2
EAN	4015573853751
Order Unit	15 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	White
Marking of poles	
Color of housing inclusive strain relief	White

Model

Number of poles	4
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP40
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05Z1Z1-F



Cable colour	White
Cable diameter	9.2 mm
Version of cable	Female - free end
Type of cord set	Connection cable
Version cable end 1	GST18i4 socket
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	Yes
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	4 m
--------------	-----

Technical drawing

Pol/pole	Aderfarbe/colour of core
L2	schwarz/black
N	blau/blue
⊕	grün-gelb/green-yellow
L1	braun/brown

.F	Farbe colour	Codierung *X* <small>Buchsenfemale</small>	Kabelfarbe / cable colour Zugentlastungsfarbe/strain relief colour
.1	schwarz black	2 N PE 1	schwarz black
.2	weiß white	2 N PE 1	weiß white
.3	grau grey	2 N PE 1	schwarz black

Kabel/cable: H05Z1Z1-F4G1,5 halogenfrei/halogenfree
Farbe/colour: siehe Tabelle/see table

Weitere Daten siehe Katalog
further data see catalog

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.207.XX63.F	XX in dm-Schritten	92.207.1063.1 = 10dm/L= 1000mm	GST18i4KSB- 15H 10SW
U2.207.XX63.F	XX in m-Schritten	U2.207.1263.1 = 12 m/L=12000mm	GST18i4KSB- 15H X10SW

Typ/type: GST18i4KSB- 15H. . SW = schwarz/black
WS = weiß/white
GR01 = grau/grey

PRE-ASSEMBLED CABLE
KONFEKT-LEITUNG
Buchse/female-free end/free end HALOGEN-FREE
Schraubanschluss/screw connection 1,5gmm 250V