




Features

- Compact and elegant design
- Suitable replacement for halogen, incandescent and compact fluorescent candle lamps
- Instant light at the flick of a switch
- Uniform light distribution
- Good colour rendering (CRI 80)
- Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
- Lower maintenance costs
- A+ energy rating

Product Overview

Product name	ToLEDo CANDLE V6 470LM 827 E14 SL
Technology	LED
Watt (Rated) (W)	5
Cap/Base	E14
Fixture rating	Open
E-number FI	4740195
Colour temperature (K)	2700
CRI (Ra)	80
Wattage (W)	5
Product EAN number	5410288269313
Warranty	3 years

Technical drawings



Data table

GENERAL DATA

Product name	ToLEDo CANDLE V6 470LM 827 E14 SL
Technology	LED
Watt (Rated) (W)	5
Cap/Base	E14
Fixture rating	Open
Performance ambient temperature Tq (°C)	25
E-number FI	4740195
Warranty	3 years

OPTICAL DATA

Luminous flux (Rated) (lm)	470
Colour temperature (K)	2700
CRI (Ra)	80

ToLEDo CANDLE V6 470LM 827 E14 SL 0026931

Lumen maintenance at end of nominal life (%)	70
--	----

ELECTRICAL DATA

Wattage (W)	5
Starting time (max) (s)	0.5
Lamp power factor	0.5
Control gear required	No
Inrush Current (A)	3
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	138

LIFETIME DATA

Average life (Rated) (h)	15000
--------------------------	-------

PHYSICAL DATA

Nominal Product Length (mm)	104
Nominal Product Diameter (mm)	35
Weight (kg)	0.061

PACKAGING

Single packaging type	Carton
Product EAN number	5410288269313
Packaging single width (cm)	4.8
Packaging single depth (cm)	4.8
DUN14 (inner)	25410288269317
Units per inner package	6
Packaging inner length / height (cm)	15.0
Packaging inner width (cm)	10.5
Packaging inner depth (cm)	15.3
DUN14 (outer)	15410288269310
Packaging outer length / height (cm)	55.2

SAFETY DATA

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No
Safety message	Not Suitable for totally enclosed fixtures