Product data sheet Spirotech

Product name

SpiroCombi -DN100 -Flange -Demount

Product properties

A demountable steel (microbubble) deaerator and dirt separator for standard flow rate (1.5 m/s) with a DN50 - DN300 PN16 flange connection

- Combined separation system removes circulating air and microbubbles effectively •
- Improve cost control and energy efficiency •
- Applicable with 50/50 Ethylene Glycol / Water (Volume) •
- . Very small particles, from 5 μm (= 0.005 mm), are separated and removed
- Dirt can be discharged while the system is in operation
- We recommend equipping the separator with shut-off valves on both sides •
- In case of severe pollution and/or maintenance, the unit is demountable •
- Constant low pressure drop •
- PN16 flange connections
- Connection diameters from DN50 DN300, larger connection diameters on request •
- Exceptional guarantee •


Article number

BD100F

Product image



Product dimensions





ETIM product data

Steel
Yes
St 37 (1.0254)
No
10 bar
Yes
No
Air/dirt
Flange
Horizontal
DN 100
50 %
Yes
Yes
475 mm

Article compression class	PN 10
Surface protection	Lacquered
Suitable for open system	No
Suitable for closed system	Yes
Suitable for solar	No
With dismountable filter	Yes
Filter volume	25 I
Magnet operating principle	No
With automatic de-aerator	Yes
With integrated replenishment automat	No
With couplers	No
Cleaning possible during operation	Yes
Material of connection	Steel
Inlet/outlet offset distance	0 mm
Flange standard	DIN

Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website.



