

Wall mounted receptacle DUO

Part number: 5603409G



MENNEKES
Elektrotechnik GmbH & Co. KG

Aloys-Mennekes-Straße 1
57399 Kirchhundem
GERMANY

www.MENNEKES.org

Product Description

- pre-wired for installation
- mechanical DUO-interlock
- switch 3p + N + PE
- X-CONTACT
- internal fixing
- 25° inclination
- enclosure base can be turned 180°
- receptacles can be locked with a padlock

Technical Details

Wall mounted receptacle DUO - Part No. 5603409G	5603409G
Product serie	DUO
Ampere	32A
Number of poles	4p
Clock position	9h
Nominal voltage AC	230V
Nominal frequency	50 - 60 Hz
Protection type IP	IP44
Contact carrier	standard
X-CONTACT	yes
Screw drive external screws	allen key, slot
Pilot contact	without pilot contact
Pilot contact switch	no
Load break switch	32A 3p + N + PE (N and PE unswitched)
DIN rail	no
Inspection window	no
Cable entry at the top	1 x M25, 1 x M32
Cable entry at the bottom	2 x M25
Enclosure base can be turned 180°	yes
Insertion direction	angled
Inclination	25°
Type of mounting	internal fixing
Highly resistant to chemicals	no
LED voltage indicator	no

Wall mounted receptacle DUO - Part No. 5603409G		5603409G
Tightening torque external screws		1.6 Nm
Lockable		yes, with a padlock up to max. 4 mm
Conductor cross-section min.		2.5 mm ²
Conductor cross-section max.		10 mm ²
IK code		IK08
Weight (net)		1400 g
Packaging unit		1 pcs
Quantity per pallet		156 pcs
EAN / identification number		4015394298038

Permissible ambient conditions

	Min.	Max.
Permissible ambient temperature	-25 °C	40 °C
Average temperature over 24 hours		35 °C

Material properties

Base	PC/ASA black [similar RAL 9005]
Upper part	PC/ASA light grey [similar RAL 7035]
Hinged lid	PC blue [similar RAL 5007]
Rotary handle	PC/ASA light grey [similar RAL 7035]
External screws	PA6 black [similar RAL 9005]

Material resistance

The material resistance overview can be found on the website in the section "Knowledge" - "Product knowledge" - "Materials".

Material and environmental properties

RoHS 2011/65/EU inkl. 2015/863/EU

✓

POP regulation (EU) 2019/1021

✓

Halogen-free

yes

Regulations and Standards

Norm

DIN EN IEC 60309-4


Declaration of Conformity

CE

Test label

CB Zertifikat, CQC, VDE

Dimensional Drawing



Drawing 1 MB 713	Amp. Poles	16			32		
		3	4	5	3	4	5
Dim. in mm	a	225	225	225	225	225	225
	b	118	118	118	118	118	118
	c	160	160	160	162	162	162
	d	208	208	208	208	208	208
	e	101	101	101	101	101	101
	f	6.4	6.4	6.4	6.4	6.4	6.4
	g	5	5	5	5	5	5
	h	238	244	243	249	249	250
	α	25			25		
	M	1x25 and 1x32			1x25 and 1x32		
	M*	2x25	2x25	2x25	2x25	2x25	2x25
Max. cable diam. (mm)		25	25	25	25	25	25
Terminal for cond. cross		2.5	2.5	2.5	2.5	2.5	2.5
section (mm²) min.-max.		—10	—10	—10	—10	—10	—10