

Product data sheet Spirotech

Product name

EVU Expansion vessel 10bar 120L, standing

Product properties

EVU-10 Universal expansion vessels with replaceable membrane, P max. 10 bar / T max. 70°C.
Expansion vessels larger than 300 liters on request.

- Tested according to Pressure Equipment Directive 2014/68/EU
- Max. temperature at connection point: 70 degrees
- Max. operating pressure: 10 bar

Article number

EVU120-10

Product image



Product dimensions

Product data sheet Spirotech

ETIM product data

| | |
|---------------------------------------|---|
| Height | 805 mm |
| Volume | 120 l |
| Colour | Other |
| Diameter | 500 mm |
| Medium temperature (continuous) | 0 - 70 °C |
| Max. operating pressure | 10 bar |
| Connection | External thread conical BSPT-R (ISO 7-1 / EN 10226-1) |
| With pressure gauge | No |
| With exchangeable membrane | Yes |
| Nominal diameter expansion connection | 1 inch (25) |
| Horizontal positioning | No |
| Suitable for central heating | Yes |
| Vertical positioning | Yes |

| | |
|--------------------------------------|--|
| With legs | Yes |
| Material membrane/bladder | Ethylene-propylene diene monomer rubber (EPDM) |
| With drain | No |
| With safety valve | No |
| With mounting material | No |
| Max. glycol mixture | 60 % |
| Suitable for tap water | No |
| Max. ethanol mixture | 60 % |
| Suitable for solar collector circuit | Yes |
| Pre-pressure | 3.5 bar |
| With fixed wall support | No |
| Suitable for cooling | Yes |

Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website

