

Data Sheet | Item Number: 706-100/509-300

Connection cable; 9-pole; with solder pin; Male connector; open-ended; Length: 3 m; Conductor cross-section: 0.25 mm²

<https://www.wago.com/706-100/509-300>



Similar to illustration



Similar to illustration

Color coding acc. to DIN VDE 47100		9 poles male Sub-D connector	
		Pin number	
White			1
Brown			2
Green			3
Yellow			4
Grey			5
Pink			6
Blue			7
Red			8
Black			9
Shield		Connected to Sub-D	

Notes

Note When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Electrical data

Operating voltage ≤ 35 VAC/VDC
 Current per wire (max.) 2 A

Connection Data

Cable type LiYCY
 Color code per DIN VDE 47100

Connection 1

Pluggable connector D-subminiature male connector
 Pole number 1 9
 Connection type System
 Wire cross-section 0.25 mm²

Connection 2

Connector	open-ended
Connection type	open-ended
Wire cross-section	0.25 mm ²

Physical data

Cable length	3 m
--------------	-----

Material data

Fire load	0 MJ
Weight	1500 g

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	FR
GTIN	4055143651660
Customs tariff number	85444290900

Product Classification

UNSPSC	26121604
ETIM 9.0	EC001855
ETIM 10.0	EC001855
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance
706-100/509-300

