

## 5PKG-2005: Bend 90° male adapter Gas 20x3/4"



### Commercial information

The PVDF press fittings for gas differ in only one significant technical aspect compared to press fittings for sanitary and heating applications. The fittings have a special O-ring that is made from the HNBR and is resistant to gas. To make this difference visible, every pressure sleeve has a yellow band. The fittings for gas should never be used for sanitary applications or heating applications. Similarly, fittings for gas should only be used in combination with the yellow HENCO multilayer pipe for gas. The Henco system for gas is only permitted in countries where a gas quality mark has been granted.

PVDF offers the user a unique combination of properties:

- Highly resistant to pressure and temperature
- Excellent mechanical strength
- Extreme flexibility: bending up to 10° is possible
- Highly resistant to chemicals and corrosion
- Embedding is possible without extra protection

#### Basic unit dimensions

Height	40 mm
Length	79 mm
Width	72 mm
Net weight	0.145 kg

#### Certificates

GASTEC, TSU, ROST

#### Applications

Gas

#### Solutions

Building installations, Industry, Oil & gas, Utility, Shipbuilding

## Technical characteristics

Material	Kunststof/messing	Outer pipe diameter connection 1	20 Millimetre
Material connection 1	Polyvinylidene fluoride (PVDF)	Zeta value	10.5
Material quality	Polyvinylidene fluoride (PVDF)	Length	78.5 Millimetre
Material quality connection 1	Polyvinylidene fluoride (PVDF) (expired)	Length of connection 1	59 Millimetre
Surface protection connection 1	Untreated	Working length connection 1	32 Millimetre
Surface treatment connection 1	Untreated	Length of connection 2	58.5 Millimetre
Material connection 2	Brass	Working length connection 2	42 Millimetre
Material quality connection 2	CuZn40Pb2 (CW617N)	Wrench width	0 Millimetre
Surface protection connection 2	Untreated	Wrench width union nut	0 Millimetre
Surface treatment connection 2	Untreated	Medium temperature (continuous)	-20 60 Degrees celsius
Shape	Bend	Max. operating pressure at 20 °C	10 Bar
Reducing	✘	Standard Dimension Ratio (SDR)	0
Eccentric	✘		
System specific	✓		
Connection 1	Press sleeve		
Contour code connection 1	TH/BE		
Nominal diameter connection 2	3/4 inch (20)		
Connection 2	External thread conical BSPT-R (ISO 7-1 / EN 10226-1)		
Main colour fitting	Black		
Material sealing	Hydrogenated acrylonitrile butadiene rubber (HNBR)		
With buffer stud	✓		
High tensile strength	✘		
Gastec QA	✓		
With thermal insulation	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✘		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✘		
KIWA certified	✘		
Gastec QA mark	✓		
KOMO certified	✘		
Type approval according to BBR/EKS	✘		