

BAP-FFV16Z05: Inox ball valve with handle, press x swivel nut Ø16 x 3/4"



Commercial information

With the BAP-FFV valve assortment, Henco offers stainless steel valves that guarantee an extra-long life, regardless of water hardness. They are also the right solution for "heavy duty" environments such as hospitals, farms, car washes, laboratories, etc. Also suitable for osmosis and demineralised water.

This stainless steel valve offers the user a unique range of benefits:

- Connections: press x swivel
- KIWA and DVGW certified
- Available in diameters from 16 to 32 mm
- With removable levers
- Equipped with Leak Before Press functionality
- With color indication for water type

Basic unit dimensions

Height	82 mm
Length	127 mm
Width	35 mm
Net weight	0.246 kg

Certificates

KIWA SE, KIWA

Applications

Potable water, Heating, Compressed air, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Housing material	Stainless steel	Medium temperature (continuous)	-10 70 Degrees celsius
Material quality	Stainless steel 316 L (1.4404)	Length of connection 1	52.5 Millimetre
Surface protection housing	None	Working length connection 1	45 Millimetre
Material ball	Stainless steel	Length of connection 2	64.3 Millimetre
Surface protection ball	None	Working length connection 2	33.5 Millimetre
Material spindle	Stainless steel	Handgrip length	12.2 Millimetre
Material primary spindle seal	Other		
Material secondary spindle seal	Other		
Nominal diameter connection 1	3/4 inch (20)		
Connection 1	Internal thread cylindrical BSPP-G (ISO 228-1)		
With coupling connection 1	✗		
Nominal diameter connection 2	DN 8		
Connection 2	Press sleeve		
With coupling connection 2	✗		
Contour code connection 2	TH/BE		
Article compression class	PN 16		
With drain valve	✗		
With drain possibility (connection)	✗		
With filter	✗		
With thermometer	✗		
Model	Straight		
With insulation shell	✗		
UL quality mark	✗		
ULC quality mark	✗		
FM quality mark	✗		
LPCB quality mark	✗		
Fire-safe	✗		
Medically clean	✗		
Grease-free	✗		
Operation	Lever handle		
Full bore	✓		
VdS quality mark	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✗		
KIWA certified	✓		
Type approval according to BBR/EKS	✗		