

# Data Sheet | Item Number: 706-100/625-100

Connection cable; 25-pole; with solder pin; Female connector; open-ended; Length: 1 m; Conductor cross-section: 0.25 mm<sup>2</sup>

<https://www.wago.com/706-100/625-100>



Color coding acc. to DIN VDE 47100		25 poles female Sub-D connector
		Pin number
White		1
Brown		2
Green		3
Yellow		4
Grey		5
Pink		6
Blue		7
Red		8
Black		9
Violet		10
Grey-Pink		11
Red-Blue		12
White-Green		13
Brown-Green		14
White-Yellow		15
Yellow-Brown		16
White-Grey		17
Grey-Brown		18
White-Pink		19
Pink-Brown		20
White-Blue		21
Brown-Blue		22
White-Red		23
Brown-Red		24
White-Black		25
Shield		Connected to Sub-D

**Notes**

Note When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

**Electrical data**

Operating voltage ≤ 125 VAC/VDC

Current per wire (max.) 2 A

Connection Data		Connection 1	
Cable type	LiYCY	Pluggable connector	D-subminiature female connector
Color code	per DIN VDE 47100	Pole number 1	25
		Connection type	System
		Wire cross-section	0.25 mm <sup>2</sup>

### Connection 2

Connector	open-ended
Connection type	open-ended
Wire cross-section	0.25 mm <sup>2</sup>

### Physical data

Cable length	1 m
--------------	-----

### Material data

Fire load	0 MJ
Weight	1.1 g

### Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

### Commercial data

PU (SPU)	1 pcs
Packaging type	Box
Country of origin	FR
GTIN	4050821835653
Customs tariff number	85444290900

### Product Classification

UNSPSC	26121609
ETIM 9.0	EC001855
ETIM 10.0	EC001855
ECCN	NO US CLASSIFICATION

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

### Downloads

#### Environmental Product Compliance

##### Compliance Search

Environmental Product  
Compliance  
706-100/625-100

