

Data Sheet | Item Number: 706-100/615-200

Connection cable; 15-pole; with solder pin; Female connector; open-ended; Length: 2 m; Conductor cross-section: 0.25 mm²

<https://www.wago.com/706-100/615-200>



Similar to illustration



Similar to illustration

Color coding acc. to DIN VDE 47100		15 poles female Sub-D connector	
		Pin number	
White			1
Brown			2
Green			3
Yellow			4
Grey			5
Pink			6
Blue			7
Red			8
Black			9
Violet			10
Grey-Pink			11
Red-Blue			12
White-Green			13
Brown-Green			14
White-Yellow			15
Shield			Connected to Sub-D

Notes

Note When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Electrical data

Operating voltage ≤ 35 VAC/VDC
 Current per wire (max.) 2 A

Connection Data

Cable type LiYCY
 Color code per DIN VDE 47100

Connection 1

Pluggable connector D-subminiature female connector
 Pole number 1 15
 Connection type System
 Wire cross-section 0.25 mm²

Connection 2

Connector	open-ended
Connection type	open-ended
Wire cross-section	0.25 mm ²

Physical data

Cable length	2 m
--------------	-----

Material data

Fire load	0 MJ
Weight	1.1 g

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

PU (SPU)	1 pcs
Packaging type	Box
GTIN	4050821835622
Customs tariff number	85444290900

Product Classification

UNSPSC	26121604
ETIM 9.0	EC001855
ETIM 10.0	EC001855
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance
706-100/615-200

