

ToLEDo Superia T8 ECG

TOLEDO SUPERIA T8 ECG 2FT 1100LM865
0027065



Product features

- 50,000 hours average rated life (L70 F50) • Last 2.5 times longer than 600mm 18W fluorescent T8 Tri-phosphor lamp • High switching cycles - 200,000X • High lumen efficacy - 147lm/W • Omni-directional light distribution and wide beam angle • Minimum and maximum operating temperature: -20°C to 55°C • Glass construction and polycarbonate end-caps • Not suitable for direct mains (AC 220-240V) or CCG/magnetic ballast • Works only with compatible electronic ballast. • Ideal for factories, parking lots, supermarkets, department stores, schools and offices.



PRODUCT OVERVIEW

Product name	TOLEDO SUPERIA T8 ECG 2FT 1100LM865
Technology	LED
Watt (Rated) (W)	7.5
General application	Museums & Galleries, Residential & Consumer, Education, Logistics & Industry, Retail, Office, Hospitality
ETIM Class	EC001959
E-number FI	4740534
Warranty	5 years
Luminous flux (lm)	1100
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Beam Angle (°)	220
Wattage (W)	7.5
Average life (Nominal) (h)	50000
Product EAN number	5410288270654

DATA TABLE

General data

Product name	TOLEDO SUPERIA T8 ECG 2FT 1100LM865
Technology	LED
Watt (Rated) (W)	7.5
General application	Museums & Galleries, Residential & Consumer, Education, Logistics & Industry, Retail, Office, Hospitality
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740534
Warranty	5 years

Optical data

Luminous flux (lm)	1100
Luminous flux (Rated) (lm)	1100
Colour temperature (K)	6500

ToLEDo Superia T8 ECG

TOLEDO SUPERIA T8 ECG 2FT 1100LM865
0027065

Light colour	Daylight
CRI (Ra)	80
Beam Angle (°)	220
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	7.5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	<2
Primary Supply/Product voltage - min (V)	20.0
Primary Supply/Product voltage - max (V)	80.0
Lamp power factor	0.82
No. Of switching cycles before premature failures	>200000
kWh per 1000 hours burning time	9

Lifetime data

Average life (Nominal) (h)	50000
Average life (Rated) (h)	50000

Physical data

Nominal Product Diameter (mm)	600
Weight (kg)	0.122

Packaging

Single packaging type	Carton
Product EAN number	5410288270654
Packaging single length / height (cm)	61.0
Packaging single width (cm)	2.9
Packaging single depth (cm)	2.9
DUN14 (outer)	15410288270651
Units per outer package	10
Packaging outer length / height (cm)	66.5
Packaging outer width (cm)	21.3
Packaging outer depth (cm)	11.5

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture