



Features

- 50,000 hours average rated life (L70 F50)
- Last 2.5 times longer than 600mm 18W fluorescent T8 Tri-phosphor lamp
- High switching cycles – 200,000X
- High lumen efficacy - 147lm/W
- Omni-directional light distribution and wide beam angle
- Minimum and maximum operating temperature: -20°C to 55°C
- Glass construction and polycarbonate end-caps
- Not suitable for direct mains (AC 220-240V) or CCG/magnetic ballast
- Works only with compatible electronic ballast
- Ideal for factories, parking lots, supermarkets, department stores, schools and offices.

Product Overview

Product name	TOLEDO SUPERIA T8 ECG 2FT 1100LM865
Technology	LED
Watt (Rated) (W)	7.5
E-number FI	4740534
Colour temperature (K)	6500
CRI (Ra)	80
Wattage (W)	7.5
Product EAN number	5410288270654
Warranty	5 years

Data table

GENERAL DATA

Product name	TOLEDO SUPERIA T8 ECG 2FT 1100LM865
Technology	LED
Watt (Rated) (W)	7.5
Performance ambient temperature Tq (°C)	25
E-number FI	4740534

TOLEDO SUPERIA T8 ECG 2FT 1100LM865 0027065

Warranty	5 years
----------	---------

OPTICAL DATA

Luminous flux (Rated) (lm)	1100
Colour temperature (K)	6500
CRI (Ra)	80
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Wattage (W)	7.5
Starting time (max) (s)	0.5
Primary Supply/Product voltage - min (V)	20.0
Lamp power factor	0.82
Control gear required	No
kWh per 1000 hours burning time	9

LIFETIME DATA

Average life (Rated) (h)	50000
--------------------------	-------

PHYSICAL DATA

Nominal Product Diameter (mm)	600
Weight (kg)	0.122

PACKAGING

Single packaging type	Carton
Product EAN number	5410288270654
Packaging single width (cm)	2.9
Packaging single depth (cm)	2.9
DUN14 (outer)	15410288270651
Packaging outer length / height (cm)	66.5

SAFETY DATA

TOLEDO SUPERIA T8 ECG 2FT 1100LM865 0027065

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No
Safety message	Suitable for totally enclosed fixture