

Presence detector
353-651521-3




- EN** Presence detector P49MR, DALI-2, BMS, 12-13 m, 360°, for flush mounting (SnapFit), Wieland gesis® 2 m Cca cable with 5-pol. connector
- NL** Aanwezigheidsmelder P49MR, DALI-2, BMS, 12-13 m, 360°, voor inbouw (SnapFit), Wieland gesis® 2 m Cca kabel met 5-polige connector
- FR** Détecteur de présence P49MR, DALI-2, BMS, 12-13 m, 360°, à encastrer (SnapFit), câble Cca Wieland gesis® de 2 m avec connecteur à 5 pôles
- DE** Präsenzmelder P49MR, DALI-2, BMS, 12-13 m, 360°, für Deckeneinbau (SnapFit), Wieland gesis® 2 m Cca Kabel mit 5-poligem Stecker
- DK** Tilstedeværelsessensor P49MR, DALI-2, BMS, 12-13 m, 360°, planforsænket (SnapFit), Wieland gesis® 2 m Cca kabel med 5-polig stik
- SE** Närvarosensor P49MR, DALI-2, BMS, 12-13 m, 360°, för infälld montering (SnapFit), Wieland gesis® 2 m Cca kabel med 5-poliga kontakter
- NO** Tilstedeværelsessensor P49MR, DALI-2, BMS, 12-13 m, 360°, til innfelt montering (SnapFit), Wieland gesis® 2 m Cca kabel med 5-polet kontakt
- IT** Rilevatore di presenza P49MR, DALI-2, BMS, 12-13 m, 360°, per montaggio a incasso (SnapFit), Wieland gesis® Cca cavo da 2 m con connettore a 5 poli
- PL** Czujnik obecności P49MR, DALI-2, BMS, 12-13 m, 360°, do montażu podtynkowego (SnapFit), Cca kabel 2 m ze złączami 5-biegunowymi Wieland gesis®
- SK** Detektor prítomnosti P49MR, DALI-2, BMS, 12-13 m, 360°, na zapustenú montáž (SnapFit), Wieland gesis® 2m Cca kábel s 5-pólovým konektorom

Wiring


Aansluitschema / Schéma de raccordement / Verdrahtung / Tilslutningsskema / Kopplingsschema / Ledningstikopling / Cablaggio / Okablowanie / Instalácia

! DALI power – OFF



Installation

Instalatie / Installation / Installation / Installation / Installation / Installasjon / Installazione / Instalacja / Instalácia





NOT REMOVABLE
(fixed ceiling)

REMOVABLE
(suspended ceiling)

1





2




OR

OR




3

a




b




4

a

! DALI power – OFF




b



* optional

Detection area

Detectiebereik / Portée de détection / Erfassungsbereich / Rækkevidde / Detekteringsområde / Overvåkningsområde / Campo di rilevamento / Obszar wykrywania / Oblast snímání




H	A Walking	B Across	C Towards	D Presence
2.5 m	∅ 13 m	∅ 11 m	∅ 3 m	∅ 5 m
3.0 m	∅ 12 m	∅ 12 m	∅ 3 m	∅ 5 m

Measured according to EN/IEC63180



Dimensions

Årmetingen / Dimensions / Abmessungen / Dimensioner / Mått / Dimensjoner / Dimensioni / Wymiary / Rozmery



Specifications

Specificaties / Specifications / Spezifikationen / Specifikationer / Specifikationer / Spesifikasjoner / Specifiche / Specyfikacje / Technické údaje

Installation		DALI-2
Configuration		BMS
Mounting height		2 – 3.5 m
Wire capacity		1.5 / 2.5 mm ²
Input voltage		via the DALI bus
Operating frequency		2.4 GHz
Maximum startup time DALI		< 1200 ms
Maximum PIR detection startup time		70 s
Maximum current consumption		10 mA
Nominal current consumption (12 V, 25 °C) Bluetooth® enabled		4 mA
Nominal current consumption (12 V, 25 °C) Bluetooth® disabled		3 mA
Maximum radio frequency power		-2 dBm
Ambient temperature		-25 – +40 °C
Protection degree		IP20
Impact resistance		IK02
Halogen free		yes
Marking		CE
Cable specifications		
Cable colour		green
Length		2 m
Wire cross-section		1.5 mm ²
Voltage		250 V
Rated current		16 A
Halogen free		yes
Ambient temperature		-5 – +70 °C
Type of connector		male, 5-pole, blue
Fireclass, CPR		Cca

App settings & more info

App-instellingen / Réglages de l'appli / App-Einstellungen / App indstillinger / Appnstillinger / App-innstillinger / Impostazioni dell'app / Ustawienia aplikacji / Nastavenia aplikácie



DALI power – ON



Bluetooth®



The specific hardware manual for this product is available in multiple languages on guide.niko.eu

LED behaviour

Ledgedrag / Comportement des LED / LED-Verhalten / LED funktioner / LED-funktioner / LED-funksjon / Comportamento del LED / Zachowanie LED / LED signalizácia



DALI power – ON

Green LED continuous on	●	Connection OK	
Green LED breathing	●	Connection OK, overrule ON	
Green LED flashing	●	Warming up*	Wait
Red LED continuous on	●	Error	More info**:
Red LED flashing	●	Warning	
Blue LED flashing	●	Walk test active	

* When Bluetooth® communication is disabled, the green LED does not flash while warming up.
** More info / Meer informatie / Plus d'info / Mehr Info / Mere info / Mer information / Mer info / Ulteriori info / Więcej informacji / Viac informácií

Support & contact

nv Niko sa
Industriepark West 40
9100 Sint-Niklaas, Belgium

www.niko.eu

EN	+32 3 778 90 80	support@niko.eu
NL	België: +32 3 778 90 80 Nederland: +31 880 15 96 10	support.be@niko.eu support.nl@niko.eu
FR	Belgique: +32 3 778 90 80 France: +33 820 20 66 25 Suisse: +41 44 878 22 22	support.be@niko.eu support.fr@niko.eu support.ch@niko.eu
DE	Deutschland: +49 7623 96697-0 Schweiz: +41 44 878 22 22 Österreich: +43 1 7965514 Belgien: +32 3 778 90 80	support.de@niko.eu support.ch@niko.eu support.at@niko.eu support.be@niko.eu
DK	+45 74 42 47 26	support.dk@niko.eu
SE	+46 8 410 200 15	support.se@niko.eu
NO	+47 66 77 57 50	support.no@niko.eu
IT	+41 44 878 22 22	support.ch@niko.eu
PL	+48 509 378 373	support.pl@niko.eu
SK	+421 2 63 825 155	support.sk@niko.eu

Niko prepares its manuals with the greatest care and strives to make them as complete, correct and up to date as possible. Nevertheless, some deficiencies may subsist. Niko cannot be held responsible for this, other than within the legal limits. Please inform us of any deficiencies in the manuals by contacting Niko customer services at support@niko.eu