



Similar to illustration

Technical data

| | |
|--------------------|----------|
| Number of spacings | 9 -times |
|--------------------|----------|

Physical data

| | |
|-------------|----------------------|
| Depth | 150 mm / 5.91 inches |
| Pin spacing | 5/5.08 mm |

Mechanical data

| | |
|----------|--|
| Suitable | for male and female connectors with CAGE CLAMP® connection |
|----------|--|

Material data

| | |
|-----------|----------|
| Fire load | 0.909 MJ |
| Weight | 30.3 g |

Commercial data

| | |
|-----------------------|----------------------------------|
| Product Group | 1 (Rail Mounted Terminal Blocks) |
| eCl@ss 10.0 | 27-14-11-92 |
| eCl@ss 9.0 | 27-14-11-92 |
| ETIM 8.0 | EC002848 |
| ETIM 7.0 | EC002848 |
| PU (SPU) | 30 (1) pcs |
| Packaging type | Box |
| Country of origin | DE |
| GTIN | 4050821858119 |
| Customs tariff number | 39269097900 |

Environmental Product Compliance

RoHS Compliance Status

Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance 280-439




Documentation

Bid Text

| | | | |
|---------|------------|-----------------|--|
| 280-439 | 19.02.2019 | xml 2.56 KB | |
| 280-439 | 11.09.2017 | doc 23.50 KB | |

Installation Notes



Inserting a male connector via multipole operating tool.