



Features

- LiFeSafe PRO TS 700 IP65 W EM3 NM DA. LiFeSafe PRO Twin Spot IP65 W EM3 NM DA is a wall mounted DALI addressable Twin Spot Non-Maintained 3Hr emergency duration with LiFePO4 battery. 2 x 350lm per head, 7W system power, IK08, IP65, Class II electrical construction. 6-year warranty

Product Overview

Product name	LIFESAFE PRO TS 700 IP65 W EM3 NM DA
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Wall surface mounted
Light source included	0038860
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office
ETIM Class	EC001957
Fixture luminous flux (lm)	700
Luminaire efficacy (lm/W)	100
Correlated colour temperature (k)	5000
CRI (Ra)	80
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	700
Luminous flux (emergency) (lm)	700
Electrical protection	Class II
Control gear type	LED driver constant current
Housing colour	White
IP rating	IP65
IK rating	IK08

LIFESAFE PRO TS 700 IP65 W EM3 NM DA 0038860

Product EAN number

5410288388601

Warranty

6 years

Technical drawings

