

UFH-ANC-05: Valve 2x3/4 -M30x1,5-KV 2



Commercial information

The UFH-ANC zone valve enables users to fully shut off the supply and return at a manifold, for example, so that they can be controlled collectively.

Basic unit dimensions

Height	58 mm
Length	55 mm
Width	35 mm
Net weight	0.218 kg

Certificates

Applications

Underfloor Heating

Solutions

Underfloor heating, Building installations, Industry, Utility

Technical characteristics

Housing material	Brass	Max. pressure difference at 20 °C	0.6 Bar
Connection 1	External thread cylindrical BSPP-G (ISO 228-1)	Medium temperature (continuous)	4 95 Degrees celsius
Connection 2	External thread cylindrical BSPP-G (ISO 228-1)		
Surface protection	Untreated		
Internally lined	Other		
Freeflow	✓		
Self-closing	✗		
Spring closing (NC)	✗		
Spring opening (NO)	✓		
Spindle and/or hand wheel rising	✓		
Connection operation	Other		
Type of shut-off valve	Control flap		
Valve control	Other		
Type of bonnet	Screwed		
Right-angled model	✗		
Bellows seal	✗		
With position indicator	✗		
With drain valve	✗		
Standard construction length	DIN		
With backflow safeguard	✗		
Suitable for liquids	✓		
Suitable for gases	✗		
Suitable for steam	✗		
Stainless steel seat ring	✗		
Spindle seal replaceable under pressure	✗		
Spindle thread not in contact with the medium	✗		
VdS quality mark	✗		
KIWA certified	✗		
Gastec QA mark	✗		
Type approval according to BBR/EKS	✗		