

ToLEDo Superia T8 CCG and AC

ToLEDo SUPERIA T8 V4 5FT 4050LM 27W 840

0027107



Product features

- A range of high performance ToLEDo Superia T8 LED tubes with reminiscent look of fluorescent tubes.
- High performance glass construction design
- High lumen output - 4050lm, with an impressive lumen efficacy of 150 lm/W
- Omnidirectional light distribution (320°) and wide beam angle (220°)
- A++ energy rating and low power consumption
- Average rated life of 50'000 hours (L70 F50)
- Lamp length - 1500mm
- High power factor 0.95
- 200,000 switching cycle
- 5 years guarantee for complete peace of mind
- Colour temperature - 4000K
- Suitable for outdoor applications in weather proof luminaires
- Compatible with electromagnetic gear and also suitable for direct mains operation (220-240V)
- No bending or discoloration over time
- No contactable metal parts, therefore no potential risk of electric shock



PRODUCT OVERVIEW

Product name	ToLEDo SUPERIA T8 V4 5FT 4050LM 27W 840
Technology	LED
Watt (Rated) (W)	27
Lamp shape	Tube, double-ended
Cap/Base	G13
Lamp finish	Frosted/Coated
General application	Hospitality, Logistics & Industry, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740527
E-number SE	8292491
Warranty	5 years
Luminous flux (lm)	4050
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Consistency (SDCM)	6
Wattage (W)	27
Dimming method	N/A
Average life (Nominal) (h)	50000
Product EAN number	5410288271071

DATA TABLE

General data

Product name	ToLEDo SUPERIA T8 V4 5FT 4050LM 27W 840
Technology	LED
Watt (Rated) (W)	27
Lamp shape	Tube, double-ended
Cap/Base	G13
Lamp finish	Frosted/Coated
General application	Hospitality, Logistics & Industry, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740527

ToLEDo Superia T8 CCG and AC

ToLEDo SUPERIA T8 V4 5FT 4050LM 27W 840
0027107

E-number SE	8292491
Warranty	5 years

Optical data

Luminous flux (lm)	4050
Luminous flux (Rated) (lm)	4050
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Consistency (SDCM)	6
Adjustable chromaticity	N
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	27
Starting time (max) (s)	0.05
Warm-up time to 60% of full light (max) (s)	< 1s => 60%
Lamp power factor	0.95
Control gear required	No
No. Of switching cycles before premature failures	>200000
Dimming method	N/A
Drive current (mA)	120
kWh per 1000 hours burning time	27

Lifetime data

Average life (Nominal) (h)	50000
Average life (Rated) (h)	50000

Physical data

Nominal Product Diameter (mm)	1500
Length base to pin Min-Max (mm) - B	1513
Max. Lamp Diameter (mm) - D	28
Weight (kg)	0.28

Packaging

Single packaging type	Carton
Product EAN number	5410288271071
Packaging single length / height (cm)	158.0
Packaging single width (cm)	4.6
Packaging single depth (cm)	4.6
DUN14 (outer)	05410288271071
Units per outer package	10
Packaging outer length / height (cm)	160.5
Packaging outer width (cm)	25.9
Packaging outer depth (cm)	12.2


ToLEDo Superia T8 CCG and AC

ToLEDo SUPERIA T8 V4 5FT 4050LM 27W 840
0027107

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture

PHOTOMETRY



TECHNICAL DRAWINGS

