



Features

- LiFeSafe PRO BH 650 IP65 C EM3 NM/MT DA is a DALI addressable LED surface or recessed LED bulkhead. Recessing mounting kit available as an accessory. Maintained or Non-Maintained, 3Hr emergency duration,. Maximum viewing distance 24m with legend kit attached. 0 to +45°C operating temperature range. 650lm emergency output, IK10, IP65, Class II electrical construction, 6-year warranty.

Product Overview

Product name	LIFESAFE PRO BH 650 IP65 C EM3 NM/MT DA
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting, Ceiling surface mounting, Wall recessed, Wall surface mounted
Light source included	0038824
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office
ETIM Class	EC001957
Fixture luminous flux (lm)	650
Luminaire efficacy (lm/W)	72
Correlated colour temperature (k)	5000
CRI (Ra)	80
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	650
Luminous flux (emergency) (lm)	650
Electrical protection	Class II
Control gear type	LED driver constant current
Housing colour	White
IP rating	IP65



LIFESAFE PRO BH 650 IP65 C EM3 NM/MT DA
0038824

IK rating	IK10
Product EAN number	5410288388243
Warranty	6 years

Technical drawings

