



Features

• LiFeSafe PRO BH IP65 C EM3 NM/MT DA BLK is a black DALI addressable LED surface or recessed LED bulkhead. Black steel recessing kit available as an accessory. Maintained or Non-Maintained, 3Hr emergency duration, complete with 4 ISO7010 Exit legends, Left, Right, Up and Down. Maximum viewing distance 30m. 0 to +45°C operating temperature range. IK10, IP65, Class II electrical construction, 6-year warranty.

Product Overview

Product name	LIFESAFE PRO BH IP65 C EM3 NM/MT DA BLK
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting, Ceiling surface mounting, Side entry, Wall recessed, Wall surface mounted
Light source included	0038821
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office
ETIM Class	EC001957
Fixture luminous flux (lm)	200
Luminaire efficacy (lm/W)	33.3
Correlated colour temperature (k)	5000
CRI (Ra)	80
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	200
Luminous flux (emergency) (lm)	200
Electrical protection	Class II
Control gear type	LED driver constant current
Housing colour	Black



LIFESAFE PRO BH IP65 C EM3 NM/MT DA BLK  
0038821

IP rating	IP65
IK rating	IK10
Product EAN number	5410288388212
Warranty	6 years

Technical drawings

