

LiFeSafe Multifix Exit Sign EX C EM3 NM/MT ST
0032018



Features

• A range of Self-test emergency lighting luminaires designed to be flexible to mount to different surfaces delivering 3 hours of emergency lighting with a viewing distance of up to 30m. Surface, recessed, suspended, wall or flag mounting options are available as kits. The product includes six ISO7010 legends: Left, Right, 2 x Up and 2 x Down and is finished in an elegant White (RAL9016) PC housing. This product offers the option to select Maintained or Non-maintained operation using the latest LiFePO4 battery technology for better charging, longer life and cleaner operation. This product has an operating temperature range from 0 to + 45°C, complies with EN 60598-2-22 and a Lifetime 30,000 hrs.

Product Overview

Product name	LiFeSafe Multifix Exit Sign EX C EM3 NM/MT ST
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting, Wall surface mounted, Ceiling surface mounting, Suspended
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office
ETIM Class	EC001957
Luminaire efficacy (lm/W)	20
Correlated colour temperature (k)	6500
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	RG0
Electrical protection	Class II
Housing colour	RAL9003
IP rating	IP20

LiFeSafe Multifix Exit Sign EX C EM3 NM/MT ST
0032018

IK rating	IK03
Product EAN number	5410288320182
Warranty	5 years

Technical drawings

