

## ToLEDo Micro-Lynx

ToLEDo MicroLynx V2 470LM 830 SL  
0029694



### Product features

- Sleek and compact design
- Low energy consumption
- Instant light at the flick of switch
- No glare thanks to frosted diffuser
- 15,000 hours rated lamp life
- Good colour rendering - CRI80
- Non-dimmable
- 3 years warranty
- The perfect lamp for cabinet lighting in kitchens, bedrooms and for displays and showcases



## PRODUCT OVERVIEW

Product name	ToLEDo MicroLynx V2 470LM 830 SL
Technology	LED
Watt (Rated) (W)	5
Type	LED exchangeable
Cap/Base	GX53
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4741146
Warranty	3 years
Luminous flux (lm)	470
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Wattage (W)	5
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288296944

## DATA TABLE

### General data

Product name	ToLEDo MicroLynx V2 470LM 830 SL
Technology	LED
Watt (Rated) (W)	5
Type	LED exchangeable
Cap/Base	GX53
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C

## ToLEDo Micro-Lynx

ToLEDo MicroLynx V2 470LM 830 SL

0029694

Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4741146
Warranty	3 years

### Optical data

Luminous flux (lm)	470
Luminous flux (Rated) (lm)	470
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

### Electrical data

Wattage (W)	5
Equivalent watt (W)	40
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Control gear required	No
No. Of switching cycles before premature failures	>100000
Dimmable	No
Inrush Current (A)	2.4
Inrush Duration (µs)	420
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	67
Max. products per 16A B Breaker	33

### Lifetime data

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

### Physical data

Nominal Product Length (mm)	75
Nominal Product Diameter (mm)	25
Weight (kg)	0.048

### Packaging

Single packaging type	Carton
Product EAN number	5410288296944
Packaging single length / height (cm)	7.6
Packaging single width (cm)	2.7
Packaging single depth (cm)	7.6

## ToLEDo Micro-Lynx

ToLEDo MicroLynx V2 470LM 830 SL


0029694

DUN14 (outer)	15410288296941
Units per outer package	6
Packaging outer length / height (cm)	16.0
Packaging outer width (cm)	9.0
Packaging outer depth (cm)	8.4


### Safety data

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

## PHOTOMETRY



## TECHNICAL DRAWINGS




ToLEDo Micro-Lynx  
*ToLEDo MicroLynx V2 470LM 830 SL*  
0029694



**SYLVANIA**

0029694



**5**  
kWh/1000h




2019/2015

# SYLVANIA

ToLEDo Micro-Lynx  
*ToLEDo MicroLynx V2 470LM 830 SL*  
0029694



0029694



**5**  
kWh/1000h



2019/2015