



Features

- Miniature self-test (DALI) emergency recessed luminaire downlight with corridor optic, non-maintained 3 hr emergency, standalone unit with inverter module and rechargeable battery (NiMH), quick and easy installation with inverter module and battery pack contained in articulated case that can pass through 40mm cutout, 219lm, 3W, IK07, beam angle 148 degrees, 230V, 50-60Hz, recharge period 24 hours, Power Factor 0.45, charge current 300mA, LxWxD (mm) 416x29x26.


Product Overview

Product name	ROUTELED II CORRIDOR DALI
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Office, Hospitality, Retail, Education
ETIM Class	EC001957
Fixture luminous flux (lm)	212
LOR (%)	100
Correlated colour temperature (k)	5000
Light colour	Cool White
CRI (Ra)	70
Colour Consistency (SDCM)	5
Colour Variation Initial (SDCM)	5
Beam Angle (°)	158
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	219
Luminous flux (emergency) (lm)	219
Electrical protection	Class II
Housing colour	RAL9016
IP rating	IP20
IK rating	IK07


ROUTELED II CORRIDOR DALI
2059463

Product EAN number	5025768594634
Warranty	5 years

Photometry



Technical drawings



Data table

GENERAL DATA	
Product name	ROUTELED II CORRIDOR DALI
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting

ROUTELED II CORRIDOR DALI 2059463

General application	Office, Hospitality, Retail, Education
Operating temperature range (°C)	0°C...+35°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001957
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	212
LOR (%)	100
Correlated colour temperature (k)	5000
Light colour	Cool White
CRI (Ra)	70
Colour Variation Initial (SDCM)	5
Colour Consistency (SDCM)	5
Beam Angle (°)	158
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	219
Luminous flux (emergency) (lm)	219
Emergency duration (h)	3

ELECTRICAL DATA

Primary Supply/Product voltage - min (V)	230
Primary Supply/Product voltage - max (V)	240
Electrical protection	Class II
Control gear required	No
Drive current (mA)	200
Nominal Frequency (Hz)	50/60Hz

PHYSICAL DATA

Housing colour	RAL9016
IP rating	IP20
IK rating	IK07
Nominal Product Length (mm)	416

ROUTELED II CORRIDOR DALI 2059463

Nominal Product Height (mm)	27
Weight (kg)	0.948
Recessed Depth (mm)	80

PACKAGING

Product EAN number	5025768594634
Packaging single length / height (cm)	21.0
Packaging single width (cm)	18.0
Packaging single depth (cm)	11.0
DUN14 (inner)	05025768594634
Units per outer package	1
Packaging outer length / height (cm)	21.0
Packaging outer width (cm)	18.0
Packaging outer depth (cm)	10.5

SAFETY DATA

Glow Wire Test (°C)	850
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	No