

Sylveo LED - Medium

SYLVEO LED 8000LM ROAD ASYMMETRIC 4K DALI

0049141



Product features

- Exterior LED floodlight, comes complete with a 1000mm cable and adjustable bracket, aluminium housing, clear glass diffuser, 8542lm, 80W, 106lm/W, 4000K, 2280mA, CRI70, 52°x117° beam angle, DALI dimmable, IP66, IK08, Class I, 50000hrs, (LxWxD) 66x290x333mm




PRODUCT OVERVIEW

Product name	SYLVEO LED 8000LM ROAD ASYMMETRIC 4K DALI
Technology	LED
Housing	Aluminium
Mount	Wall surface mounted
Fixture rating	Enclosed
General application	Logistics & Industry
ETIM Class	EC001744
E-number FI	4579199
E-number SE	7764819
Warranty	5 years
Useful luminous flux (Fuse)	8542
Fixture luminous flux (lm)	8542
Luminaire efficacy (lm/W)	107
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	70
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	52 x 117
Glare control	< 18
Photobiological Risk Group	RG1
Total power consumption (W)	80
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Dimming method	DALI
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9006 - Aluminium
IP rating	IP66
IK rating	IK08
Product EAN number	5410288491417

Sylveo LED - Medium

SYLVEO LED 8000LM ROAD ASYMMETRIC 4K DALI
0049141

PHOTOMETRY



TECHNICAL DRAWINGS

