

Optix MPO 1200 Direct

OPTIX SURFACE 1200 MPO D HO 4000K DALI EM

2021667



Product features

- OPTIX SURFACE 1200 MPO D HO 4000K DALI EM is a high efficacy low glare surface or suspended LED Linear luminaire with Micro Prismatic diffuser, with direct light distribution, luminaire dimensions: 1200x200x50mm, Sylvania White body colour (RAL9016), IP20, IK07, DALI Dimmable, 3hr maintained emergency version, low LED flicker (+/-5%), Neutral White (4000K) LED Colour Temperature, 3550lm luminous flux, 33W power consumption, 107lm/W system efficacy, CRI>80, SDCM 3 (3-step MacAdam ellipse) LED Colour Consistency, UGR<20, Luminance at 65° < 3000 cd/m², lifespan: 58,000 hours L90B10, photobiological safety risk group 1. Electrical protection Class I.




PRODUCT OVERVIEW

Product name	OPTIX SURFACE 1200 MPO D HO 4000K DALI EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
General application	Education, Office
ETIM Class	EC002892
Warranty	5 years
Useful luminous flux (Fuse)	3550
Fixture luminous flux (lm)	3550
Luminous flux (lm)	3550
Luminaire efficacy (lm/W)	107
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 20
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	80
Total power consumption (W)	33
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768216673

Optix MPO 1200 Direct

OPTIX SURFACE 1200 MPO D HO 4000K DALI EM
2021667

PHOTOMETRY



TECHNICAL DRAWINGS

