



Color: ■ gray

Similar to illustration

#### Electrical data

Operating voltage	250 VAC
Power (max.)	0.6 W
Thermal resistance	140 K/W
Tolerance	±1 %
Resistor type/design	DIN 0207

#### Safety and protection

Rated impulse withstand voltage	4 kV
Pollution degree	3
Protection type	IP20

#### Connection Data

##### Connection 1

Actuation type	Operating tool
----------------	----------------

#### Physical data

Width	10 mm / 0.394 inches
-------	----------------------

### Material data

Color	gray
Insulation material (main housing)	Polyamide (PA66)
Material group	I
Flammability class per UL94	V0
Fire load	0.087 MJ
Weight	4.3 g

### Environmental requirements

Ambient temperature (operation)	-25 ... +70 °C
Processing temperature	-35 ... +85 °C

### Standards and Specifications

Standards/specifications	EN 60947-7-1 EN 60664-1 EN 60557
--------------------------	--

### Commercial data

Product Group	1 (Rail Mounted Terminal Blocks)
PU (SPU)	50 pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454196028
Customs tariff number	85366990990

### Product Classification

UNSPSC	39121402
ETIM 9.0	EC002018
ETIM 10.0	EC002018
ECCN	NO US CLASSIFICATION

### Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

### Downloads

#### Environmental Product Compliance

##### Compliance Search

Environmental Product  
Compliance  
280-803/281-577

