



5-FLEX32: Hencoflex 2x Ø32x3 5m



Commercial information

Certificates

Applications

Potable water, Heating, Cooling, Compressed air, Demi Water, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Material inner layer	Plastic	Commercial length	5 Metre
Material intermediate layer	Aluminium	Outer pipe diameter	32 Millimetre
Material outer layer	Plastic	Wall thickness	3 Millimetre
Glass-fibre reinforced		Medium temperature (continuous)	- Degrees celsius 10 9 5
	✘		
Diffusion-proof	✓	Max. medium temperature (momentarily)	95 Degrees celsius
System specific	✓	Max. operating pressure at 20 °C	16 Bar
Jacket colour	Black	Wall roughness	0.00 Millimetre 7
Flexible	✘	Expansion coefficient	0.02 Millimetre per metre Kelvin 5
Suitable for surface mounting	✓	Min. bending radius	0 Millimetre
Pipe colour	Black	Min. bending radius without tools	0 Millimetre
With mantle pipe	✓	Outer diameter mantle pipe	125 Millimetre
With heating cable	✘	Lambda value	0.29 Watt per meter Kelvin 3
Colour outer sheath	Black	Outer diameter thermal insulation	0 Millimetre
With thermal insulation	✓	Outer width rectangular insulation	0 Millimetre
Shape of insulation	Round	Outer height rectangular insulation	0 Millimetre
Colour of thermal insulation	Grey		
Capped	✘		
UV resistant	✓		
Type approval according to BBR/EKS	✘		

Related products