


## 2S-1604K: Sanitair muurplaat binnendraad kort 16x1/2"



### Commerciële informatie

The Henco Vision fitting is entirely made from PVDF, a high-performance material. Some key advantages of these push fittings are:

- Fast and easy installation
- Pressing machines or wrenches are not required
- For both sanitary and central heating applications
- 100% embedding guaranteed

#### Advantages of PVDF

- Highly resistant to pressure and temperature
- Excellent mechanical strength
- Extreme flexibility: bending up to 10° is possible
- Perfectly suited for drinking water and foodstuffs
- Embedding is possible without extra protection
- Highly resistant to chemicals and corrosion

#### Dimensies basiseenheid

|               |                                      |
|---------------|--------------------------------------|
| Hoogte        | 43 mm                                |
| Lengte        | 79 mm                                |
| Breedte       | 52 mm                                |
| Netto gewicht | 0,162 kg                             |
| SCIP nummer   | 6b5ef4aa-b2e5-4f8c-8ef1-685f34c18f66 |

#### Certificaten

KIWA, KOMO, DVGW Wasser, GOST-R, QB (CSTBat), ATG, WRAS, ÖVGW Wasser, AFNOR, SINTEF, ETA, STF, RISE, ACS, PZH, TSU, EMI

#### Toepassingen

Drinkwater, Verwarming, Koeling, Sanitair

#### Oplossingen

Gebouwinstallaties, Industrie, Infra

## Technische kenmerken

|                        |                        |                                     |                       |
|------------------------|------------------------|-------------------------------------|-----------------------|
| Materiaal behuizing    | Messing                | Uitwendige buisdiameter aansluiting | 16 Millimeter         |
| Materiaal behuizing    | Messing                | Mediumtemperatuur (continu)         | -10 70 Graden Celsius |
| Oppervlaktebescherming | Onbehandeld            | Max. werkdruk bij 20°C              | 10 bar                |
| Systeemgebonden        | ✓                      |                                     |                       |
| Aansluiting            | Insteek (push-fitting) |                                     |                       |
| KIWA-keur              | ✓                      |                                     |                       |