

## WBS-1604: Wall box 2 pair Red/Blue Compression 1/2"Fx16mm



## Commercial information

## Wall box

**Solutions** 

- High-quality corrosion-proof built-in box made of plastic.
- Box in a neutral colour with a blue and red cover } Small dimensions for easy grinding (95x33x40 mm).
- Can also be easily combined with drywalls on steel profiles.
- Homogeneous closure for installation in masonry or plastering.

  Fitted with a groove to hold the pipe sleeve in place and ensure connection to the pipe.

  The built-in box can be opened quickly and easily.

  The pipe and coupling can be easily accessed without damaging the wall.

- Suited for heating and sanitary applications.
  Corrosion-proof, for a perforated steel mounting bracket.
- Inter-axis distances of 40, 50, 80, 120 and 153 mm, indicated on the mounting bracket.
- Ready for all common H-blocks and sanitary faucets.

Building installations, Industry, Utility, Shipbuilding

- Handy mounting rail available as accessory for hollow drywalls or floor levelling screeds.
- Available in 16 and 20 mm press fitting and 16 mm screw fitting.

Basic unit dimensions		
Height	48 mm	
Length	300 mm	
Width	100 mm	
Net weight	0.950 kg	
Certificates		
KIWA, KOMO, ATG, ÖN EN 21003-	2/-3, ÖVGW Wasser, ETA, WRAS, GOST-R, PZH, ITC, TSU, EMI	
Applications		
Potable water, Heating, Cooling, Sar	nitary	



## **Technical characteristics**

Housing material	Brass	Medium temperature (continuous)	-10 70 Degrees celsius
Surface protection	Untreated	Max. operating pressure at 20 °C	10 Bar
Shape	Straight		
Thread size	1/2 inch		
System specific	✓		
Connection	Press sleeve		
KIWA certified	✓		

