



Features

- LED replacement for compact fluorescent Lynx-DE lamps 30,000 hours average rated life (L70 F50) 3 years warranty Quick, simple and safe replacement without rewiring Direct retrofit – easiest way to upgrade existing luminaires to LED technology Suitable for electronic ballast/ ECG ballast and direct mains 220-240V AC operation Compact and durable construction Minimum and maximum operating temperature: -10°C to 40°C Low energy consumption and no flickering Ideal for commercial and residential applications including offices, hotels, restaurants, warehouses, supermarkets, corridors, in addition to living rooms, kitchens and garages Warning: ToLEDo Lynx DE lamps are not suitable for magnetic ballast/ CCG operation

Product Overview

Product name	ToLEDo DE 1000LM G24Q 840 SL
Technology	LED
Cap/Base	G24q-3
Fixture rating	Open
General application	Hospitality, Logistics & Industry, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740779
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Wattage (W)	10
Power consumption (W)	10
Average life (Nominal) (h)	30000
Product EAN number	5410288280615
Warranty	3 years

ToLEDo DE 1000LM G24Q 840 SL 0028061

Useful luminous flux (#use)	1000
-----------------------------	------

Data table

GENERAL DATA

Product name	ToLEDo DE 1000LM G24Q 840 SL
Technology	LED
Cap/Base	G24q-3
Fixture rating	Open
General application	Hospitality, Logistics & Industry, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740779
Warranty	3 years

OPTICAL DATA

Useful luminous flux (#use)	1000
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Power consumption (W)	10
Wattage (W)	10
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	0.5
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.93

ToLEDo DE 1000LM G24Q 840 SL 0028061

Control gear required	No
No. Of switching cycles before premature failures	>100000
Inrush Current (A)	20
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	7
Max. products per 16A C Breaker	11
Max. products per 20A C Breaker	14

LIFETIME DATA

Average life (Nominal) (h)	30000
Average life (Rated) (h)	30000

PHYSICAL DATA

Nominal Product Length (mm)	164
Nominal Product Diameter (mm)	35
Weight (kg)	0.09

PACKAGING

Product EAN number	5410288280615
Packaging single length / height (cm)	17.2
Packaging single width (cm)	3.6
Packaging single depth (cm)	3.6
DUN14 (inner)	15410288280612
Units per outer package	10
Packaging outer length / height (cm)	19.2
Packaging outer width (cm)	7.8
Packaging outer depth (cm)	17.5

SAFETY DATA

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes

ToLEDo DE 1000LM G24Q 840 SL
0028061

Suitable for household illumination

Yes

Safety message

Not Suitable for totally enclosed fixtures