

Product data sheet

Item No. 92.207.5063.2

Cable assembly

geis® Connection cable female - free end; length: 5m; type GST18I4; 4-pole; 250/400 V / 16 A; colour of coding: white with white strain-relief; cable: H05Z1Z1-F 4G1,5, colour: white



| | |
|------------|---------------|
| Item No. | 92.207.5063.2 |
| EAN | 4015573853829 |
| Order Unit | 10 Piece(s) |

Certificates / Approvals



Technical data

General

| | |
|--|--------|
| Rated current | 16 A |
| Rated voltage | 400 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 2 |
| Mechanical coding | Code 1 |
| Interlockable | Yes |
| Color of coding/ contact carrier | White |
| Marking of poles | |
| Color of housing inclusive strain relief | White |

Model

| | |
|---------------------------------|-------------------------------------|
| Number of poles | 4 |
| Nominal cross section conductor | 1.5 mm ² |
| Degree of protection (IP) | IP40 |
| Wire strip length | 9 mm |
| sheath strip length | 35 mm |
| Preparation of conductor ends | Ultrasonically compressed wire ends |
| Cable type | H05Z1Z1-F |



| | |
|---------------------|-------------------|
| Cable colour | White |
| Cable diameter | 9.2 mm |
| Version of cable | Female - free end |
| Type of cord set | Connection cable |
| Version cable end 1 | GST18i4 socket |
| Version cable end 2 | Free end |

Material

| | |
|--|------------|
| Surface finish | Tin-plated |
| Halogen free | Yes |
| Continuous temperature of cable | 70 °C |
| Insulation components continuous temperature | 100 °C |

Dimensions

| | |
|--------------|-----|
| Total length | 5 m |
|--------------|-----|

Technical drawing

| Pol/pole | Aderfarbe/colour of core |
|----------|--------------------------|
| L2 | schwarz/black |
| N | blau/blue |
| ⊕ | grün-gelb/green-yellow |
| L1 | braun/brown |

| .F | Farbe colour | Codierung *X* Buchse female | Kabelfarbe / cable colour Zugentlastungsfarbe/strain relief colour |
|----|---------------|-----------------------------|--|
| .1 | schwarz black | 2 N PE 1 | schwarz black |
| .2 | weiß white | 2 N PE 1 | weiß white |
| .3 | grau grey | 2 N PE 1 | schwarz black |

| Teile-Nr. part-no. | L | Beispiel (Farbe: schwarz) example (colour: black) | Typ type |
|--------------------|--------------------|---|-----------------------|
| 92.207.XX63.F | XX in dm-Schritten | 92.207.1063.1 = 10dm/L= 1000mm | GST18i4KSB- 15H 10SW |
| U2.207.XX63.F | XX in m-Schritten | U2.207.1263.1 = 12 m/L=12000mm | GST18i4KSB- 15H X10SW |

Kabel/cable: H05Z1Z1-F4G1,5 halogenfrei/halogenfree
Farbe/colour: siehe Tabelle/see table

Weitere Daten siehe Katalog
further data see catalog

Typ/type: GST18i4KSB- 15H. . SW = schwarz/black
WS = weiß/white
GR01 = grau/grey

PRE-ASSEMBLED CABLE KONFEKT LEITUNG
Buchse/female-Freies Ende/free end HALOGEN-FREE
Schraubanschluss/screw connection 1,5gmm 250V